



Design: Svein Knudsen / Andrew Smith. Attractive, round luminaire that can be mounted to both walls and ceilings, and both indoors and outdoors. Made of die-cast powder-coated aluminium. Flat diffuser made of UV-stabilised opal polycarbonate. Many variants with both sensors and wireless control, as well as various lumen packages. IP65 and vandal-resistant rating IK10.

Produkt- und Umgebungsbilder



Artikel	Schutzklasse	Controller	Montage/Anschluss	Größe
 644867 Canto 2000 Schwarz 1520lm 3000K Ra>80 Sensor 14W LED 109 lm/W SDCM:3 L70/B50>100.000 Beam: 110°, Direkt, Opal	Klasse I IP65 IK10	Sensor	Anbau, Indoor / Outdoor Anschlussklemme	Ø325 x H120
 644866 Canto 2000 Schwarz 1520lm 3000K Ra>80 Phasenabschnitt 14W LED 109 lm/W SDCM:3 L70/B50>100.000 Beam: 110°, Direkt, Opal	Klasse I IP65 IK10	Phasenabschnitt	Anbau, Indoor / Outdoor Anschlussklemme	Ø325 x H120
 643867 • Canto 2000 Graphit 1400lm 3000K Ra>80 Sensor 14W LED 100 lm/W SDCM:3 L70/B50>100.000 Beam: 110°, Direkt, Opal	IP65 IK10	Sensor	Anbau, Indoor / Outdoor Anschlussklemme	Ø325 x H120
 643866 Canto 2000 Graphit 1520lm 3000K Ra>80 Phasenabschnitt 14W LED 109 lm/W SDCM:3 L70/B50>100.000 Beam: 110°, Direkt, Opal	Klasse I IP65 IK10	Phasenabschnitt	Anbau, Indoor / Outdoor Anschlussklemme	Ø325 x H120
 641866 Canto 2000 Weiss 1550lm 3000K Ra>80 Phasenabschnitt 14W LED 111 lm/W SDCM:3 L70/B50>100.000 Beam: 110°, Direkt, Opal	Klasse I IP65 IK10	Phasenabschnitt	Anbau, Indoor / Outdoor Anschlussklemme	Ø325 x H120

• = Lieferzeit auf Anfrage.