



Attractive, square luminaire with direct and indirect light that can be mounted to both walls and ceilings, and both indoors and outdoors. Made of die-cast powder-coated aluminium. Flat diffuser with indirect light made of UV-stabilised opal polycarbonate. Several light source variants and sensors, and wireless control. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable terminal block. IP65 and vandal-resistant rating IK10.

Produkt- und Umgebungsbilder



Artikel		Schutzklasse	Controller	Montage/Anschluss	Größe
	623839 Sidewalk 2000 Graphit 1250lm 3000K Ra>80 Nicht dimmbar 19W LED 66 lm/W SDCM:3 L70/B50>100.000 Beam: 110°, Direkt, Opal	Klasse I IP65 IK10	Nicht dimmbar	Anbau, Indoor / Outdoor Anschlussbox	L300 x W300 x H87
	633839 Sidewalk 2000 Graphit 1300lm 3000K Ra>80 Sensor 14W LED 93 lm/W SDCM:3 L70/B50>100.000 Beam: 110°, Direkt, Opal	Klasse I IP65 IK10	Sensor	Anbau, Indoor / Outdoor Anschlussbox	L300 x W300 x H87
	644832 Sidewalk 2000 Schwarz 1380lm 4000K Ra>80 Phasenabschnitt 14W LED 99 lm/W SDCM:3 L70/B50>100.000 Beam: 110°, Direkt, Opal	Klasse I IP65 IK10	Phasenabschnitt	Anbau, Indoor / Outdoor Anschlussbox	L300 x W300 x H87
	643833 Sidewalk 2000 Graphit 1500lm 4000K Ra>80 Sensor 14W LED 107 lm/W SDCM:3 L70/B50>100.000 Beam: 110°, Direkt, Opal	Klasse I IP65 IK10	Sensor	Anbau, Indoor / Outdoor Anschlussbox	L300 x W300 x H87
	643832 Sidewalk 2000 Graphit 1500lm 4000K Ra>80 Phasenabschnitt 14W LED 107 lm/W SDCM:3 L70/B50>100.000 Beam: 110°, Direkt, Opal	Klasse I IP65 IK10	Phasenabschnitt	Anbau, Indoor / Outdoor Anschlussbox	L300 x W300 x H87