

# Fagernes



Fagernes is a modern classic luminaire for both outdoor and indoor use. The light source is recessed and provides a glare free indirect light. It is easy to install with wall bracket, quick connectors, and loop in/out for both hidden or surface mounted cabling. Fagernes is Phase cut dimmable. Fagernes is available in two different sizes.

## Produkt- und Umgebungsbilder



| Artikel                                                                           |                                                                                    | Schutzklasse     | Controller      | Montage/Anschluss      | Größe              |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------|-----------------|------------------------|--------------------|
|  | 630060                                                                             | <b>Klasse II</b> | Phasenabschnitt | Wand, Indoor / Outdoor | W160 x H224 x D100 |
|                                                                                   | <b>Fagernes Schwarz Mini 270lm</b>                                                 | <b>IP44</b>      |                 | Anschlussklemme        |                    |
|                                                                                   | <b>2700K Ra&gt;80 Phasenabschnitt</b>                                              | <b>IK07</b>      |                 |                        |                    |
|                                                                                   | <b>9W LED</b>                                                                      |                  |                 |                        |                    |
|                                                                                   | 30 lm/W SDCM:3<br>L70/B50>100.000, L90/B10>50.000<br>Beam: 110°, Direkt, Glas klar |                  |                 |                        |                    |
|  | 630061                                                                             | <b>Klasse II</b> | Phasenabschnitt | Wand, Indoor / Outdoor | W200 x H280 x D125 |
|                                                                                   | <b>Fagernes Schwarz 280lm 2700K</b>                                                | <b>IP44</b>      |                 | Anschlussklemme        |                    |
|                                                                                   | <b>Ra&gt;80 Phasenabschnitt</b>                                                    | <b>IK07</b>      |                 |                        |                    |
|                                                                                   | <b>9W LED</b>                                                                      |                  |                 |                        |                    |
|                                                                                   | 31 lm/W SDCM:3<br>L70/B50>100.000, L90/B10>50.000<br>Beam: 110°, Direkt, Glas klar |                  |                 |                        |                    |
|  | 630101                                                                             | <b>Klasse II</b> | Phasenabschnitt | Wand, Outdoor          | W200 x H280 x D125 |
|                                                                                   | <b>Fagernes Schwarz 750lm 3000K</b>                                                | <b>IP44</b>      |                 | Anschlussklemme        |                    |
|                                                                                   | <b>Ra&gt;80 Phasenabschnitt</b>                                                    | <b>IK07</b>      |                 |                        |                    |
|                                                                                   | <b>12W LED</b>                                                                     |                  |                 |                        |                    |
|                                                                                   | 63 lm/W SDCM:3<br>L70/B50>100.000<br>Beam: 110°, Direkt, Glas klar                 |                  |                 |                        |                    |