



Powerful in-ground luminaires for decorative and functional lighting of facades, gardens, patios, stairs and walls. Approved for 2000 kg load. Nemo II comes in symmetric versions with deep black reflectors for very low glare, and asymmetric versions that directs the light toward a facade or a wall. Nemo Siriak gives a decorative light along patios and facades.

Nemo II / Siriak



Produkt- und Umgebungsbilder



Artikel	Schutzklasse	Controller	Montage/Anschluss	Größe
 630070 Nemo II Mini 170lm 3000K Ra>80 Phasenabschnitt 4W LED 43 lm/W SDCM:3 L80/B20>50.000 Beam: 32°, Direkt, Linse	Klasse I IP67 IK10	Phasenabschnitt	Einbau, Indoor / Outdoor Kabel 1m	Ø110 x H100
 630071 Nemo II Mini Asymmetrisch 160lm 3000K Ra>80 Phasenabschnitt 4W LED 40 lm/W SDCM:3 L80/B20>50.000 Asymmetrisch, Linse	Klasse I IP67 IK10	Phasenabschnitt	Einbau, Indoor / Outdoor Kabel 1m	Ø110 x H100
 630072 Nemo II Midi 460lm 3000K Ra>80 Phasenabschnitt 9W LED 51 lm/W SDCM:3 L80/B20>50.000 Beam: 32°, Direkt, Linse	Klasse I IP67 IK10	Phasenabschnitt	Einbau, Indoor / Outdoor Kabel 1m	Ø130 x H110
 630073 Nemo II Midi Asymmetrisch 430lm 3000K Ra>80 Phasenabschnitt 9W LED 48 lm/W SDCM:3 L80/B20>50.000 Asymmetrisch, Linse	Klasse I IP67 IK10	Phasenabschnitt	Einbau, Indoor / Outdoor Kabel 1m	Ø130 x H110
 630075 Nemo Siriak 24lm 3000K Ra>80 Phasenabschnitt 4W LED 6 lm/W SDCM:3 L80/B20>50.000 Direkt, Linse	Klasse I IP67 IK10	Phasenabschnitt	Einbau, Indoor / Outdoor Kabel 1m	Ø110 x H100