



Kjevik is a solid bollard for public spaces, paths and parks. It has a very high lumen output, with low energy consumption. The light distribution is wide and precise with all the light below the horizontal plane, therefore no light pollution in a safe and glare-free environment. Classic design blends in with all surroundings. A 180°-degree shield is available as accessory and is perfect for paths or other places where light should be restricted to a semi-circle.

Produkt- und Umgebungsbilder



Artikel	Schutzklasse	Controller	Montage/Anschluss	Größe
 623801 [•] Kjevik Schwarz 2060lm 3000K Ra>80 DALI-2 26W LED 79 lm/W SDCM:2 L90/B10>100.000 Direkt,	Klasse II IP66 IK10	DALI-2	Outdoor	Ø200 x H1010
 623800 Kjevik Schwarz 2060lm 3000K Ra>80 Nicht dimmbar 26W LED 79 lm/W SDCM:2 L90/B10>100.000 Direkt,	Klasse II IP66 IK10	Nicht dimmbar	Outdoor	Ø200 x H1010
Zubehör				
 623804 Kjevik Schwarz 180° Abschirmung				L178 x W89 x H112
 8249042067 Erdanker				Ø155 x L248 x W108 x H450
 8249042070 Erdanker für Beton				Ø155 x H450

[•] = Lieferzeit auf Anfrage.