

Hurdal Connect



Hurdal Connect is a compact and stylish ceiling and wall luminaire featuring an integrated SG Connect sensor for smart and energy-efficient lighting control. The sensor switches the light on when motion is detected and off after a defined time period, delivering significant energy savings. A built-in daylight sensor can be activated to maintain the desired light level at all times. Configuration is simple via the SG Connect Commissioning App, and the luminaire can be used as a standalone unit or as part of a larger system that can easily be expanded or reconfigured as needed. Hurdal Connect combines high performance with easy installation. It mounts directly on ceilings or walls, with cable entry at both ends and in the middle, and through-wiring ensures quick and efficient connection. The luminaire is IP44-rated and features a robust steel housing with aluminum end caps for long-lasting and reliable operation.

Hurdal Connect



Produkt- und Umgebungsbilder





Artikel	Schutzklasse	Controller	Montage/Anschluss	Größe
 113126 Hurdal Connect 600 Weiss 1590lm 3000K Ra>80 Connect 12W LED 133 lm/W SDCM:3 L80/B20>100.000, L90>50.000 Direkt, Opal	Klasse I IP44	Connect	Anbau, Indoor 3-polige Anschlussklemme mit Durchgangsverdrahtung 3×2,5 mm ²	L600 x W72 x H76
 113127 Hurdal Connect 1200 Weiss 3460lm 3000K Ra>80 Connect 24W LED 144 lm/W SDCM:3 L80/B20>100.000, L90>50.000 Direkt, Opal	Klasse I IP44	Connect	Anbau, Indoor 3-polige Anschlussklemme mit Durchgangsverdrahtung 3×2,5 mm ²	L1200 x W72 x H76
 113128 Hurdal Connect 1500 Weiss 4640lm 3000K Ra>80 Connect 31W LED 150 lm/W SDCM:3 L80/B20>100.000, L90>50.000 Direkt, Opal	Klasse I IP44	Connect	Anbau, Indoor 3-polige Anschlussklemme mit Durchgangsverdrahtung 3×2,5 mm ²	L1500 x W72 x H76