



Design: Christian Hvidt. Mast or wall-mounted (600 mm diameter) IP66 LED luminaire. Base and top made of die-cast aluminium, inner diffuser made of PMMA opal and outer optics made of polycarbonate (PC). Grey or black base and top. Complete with LED driver for operation of LED light sources mounted to component rail with internal connector/lampholder and pre-mounted with five-metre connection cable. Prepared for mounting on 60 mm or designer mast. Safety class II.

Produkt- und Umgebungsbilder



Artikel		Schutzklasse	Controller	Montage/Anschluss	Größe
	8246090630	Klasse II	Nicht dimmbar	Mast - top (Ø60mm), Outdoor	Ø600 x H291
	Place Schwarz 2410lm 3000K Ra>80	IP66		Anschlussleitung 2x1mm² 6m	
	Nicht dimmbar	IK10			
	21W LED				
	115 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Direkt,				
	8246088215	Klasse II	DYNADIM	Mast - top (Ø60mm), Outdoor	Ø600 x H291
	Place Grau 2410lm 3000K Ra>80	IP66		Anschlussleitung 2x1mm² 6m	
	DYNADIM	IK10			
	21W LED				
	115 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Direkt,				
	8246087999	Klasse II	Nicht dimmbar	Mast - top (Ø60mm), Outdoor	Ø600 x H291
	Place Grau 2410lm 3000K Ra>80	IP66		Anschlussleitung 2x1mm² 6m	
	Nicht dimmbar	IK10			
	21W LED				
	115 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Direkt,				
	8246090614	Klasse II	DYNADIM	Mast - top (Ø60mm), Outdoor	Ø600 x H291
	Place Schwarz 2510lm 4000K Ra>80	IP66		Anschlussleitung 2x1mm² 6m	
	DYNADIM	IK10			
	28W LED				
	90 lm/W SDCM:3 L90/B10>50.000, L70/B10>100.000 Direkt,				
	8246090643	Klasse II	Nicht dimmbar	Mast - top (Ø60mm), Outdoor	Ø600 x H291
	Place Schwarz 2530lm 4000K Ra>80	IP66		Anschlussleitung 2x1mm² 6m	
	Nicht dimmbar	IK10			
	21W LED				
	120 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Direkt,				
	8246088228	Klasse II	DYNADIM	Mast - top (Ø60mm), Outdoor	Ø600 x H291
	Place Grau 2530lm 4000K Ra>80	IP66		Anschlussleitung 2x1mm² 6m	
	DYNADIM	IK10			
	21W LED				
	120 lm/W SDCM:3 L90/B10>50.000, L70/B10>100.000 Direkt,				



Artikel		Schutzklasse	Controller	Montage/Anschluss	Größe
	8246087407	Klasse II	Nicht dimmbar	Mast - top (Ø60mm), Outdoor	Ø600 x H291
	Place Grau 2530lm 4000K Ra>80	IP66		Anschlussleitung 2x1mm² 6m	
	Nicht dimmbar	IK10			
	21W LED				
	120 lm/W SDCM:3 L90/B10>50.000, L80/B10>100.000 Direkt,				
Zubehör					
	8249044492				L350 x W175 x H150
	Place Wandarm Schwarz Wandarm				
	8249044489				L350 x W175 x H150
	Place Wandarm Grau Wandarm				