



Design: Svein Knudsen / Andrew Smith. Attractive, round wall luminaire with half-diffuser and four slits for indirect light that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. IP65 and vandal-resistant rating IK10.

Tardo



Produkt- und Umgebungsbilder



Artikel		Schutzklasse	Controller	Montage/Anschluss	Größe
	633897	Klasse I	Sensor	Anbau, Indoor / Outdoor	Ø325 x D105
	Tardo 2000 Graphit 870lm 3000K	IP65		Anschlussklemme	
	Ra>80 Sensor	IK10			
	14W LED				
	62 lm/W SDCM:3 L70/B50>100.000 Beam: 120°, Direkt/Indirekt, Opal				
	633896	Klasse I	Phasenabschnitt	Anbau, Indoor / Outdoor	Ø325 x D105
	Tardo 2000 Graphit 870lm 3000K	IP65		Anschlussklemme	
	Ra>80 Phasenabschnitt	IK10			
	14W LED				
	62 lm/W SDCM:3 L70/B50>100.000 Beam: 120°, Direkt/Indirekt, Opal				
Zubehör					
	AK100				
	Anti-Vandalismus-Schlüssel				