



Farm 66 is a very hardy luminaire, especially suitable for pig farms and the like. The LED compartment has an extra high protection rating to withstand ammonia gasses in such environments. The luminaire housing is made of hard UV-stabilised and anti-chemical coated polycarbonate. The coating is resistant to ammonia, washing detergents* etc, and makes it suitable also for car wash halls and similar. It is easy to install by just snapping into mounting clips and using the unique one-hand closing mechanism at both ends. The looping options with double cable gland in each end and through wiring gives full flexibility for larger installations. * Farm 66 is resistant to aqueous salt solutions up to about 60°C and diluted acids. It has limited resistance to alcohols, aliphatic hydrocarbons, and diluted alkalis, and is not resistant to concentrated mineral acids and alkalis, ammonia, amines, aromatic and/or halogenated hydrocarbons, esters, ethers, ketones, or solvents such as methyl ethylketone, tetrahydrofuran, toluene, and dimethyl-formamide.

Produkt- und Umgebungsbilder



Artikel	Schutzklasse	Controller	Montage/Anschluss	Größe
 120012 Farm 66 1500 Grau 5860lm 4000K Ra>80 DALI-2 / Push Dim 43W LED 136 lm/W SDCM:3 L90/B50>50.000 Direkt, Opal	Klasse I IP66 IK08	DALI-2 / Push Dim	Anbau, Indoor 7-polige Anschlussbox mit Durchgangsverdrahtung 5 × 2,5 mm² (+DALI)	L1460 x W112 x H67
 120014 Farm 66 Pro 1500 Grau 9820lm 4000K Ra>80 DALI-2 / Push Dim 65W LED 151 lm/W SDCM:3 L80/B10>100.000 Direkt, Opal	Klasse I IP66 IK08	DALI-2 / Push Dim	Anbau, Indoor 7-polige Anschlussklemme mit Durchgangsverdrahtung 5 × 2,5 mm² (+DALI)	L1460 x W112 x H67
 120009 Farm 66 1200 Grau 4030lm 4000K Ra>80 Nicht dimmbar 34W LED 119 lm/W SDCM:3 L90/B50>50.000 Direkt, Opal	Klasse I IP66 IK08	Nicht dimmbar	Anbau, Indoor 5-polige Anschlussbox mit Durchgangsverdrahtung 5 × 2,5 mm²	L1174 x W112 x H67
 120010 Farm 66 1500 Grau 5720lm 4000K Ra>80 Nicht dimmbar 47W LED 122 lm/W SDCM:3 L90/B50>50.000 Direkt, Opal	Klasse I IP66 IK08	Nicht dimmbar	Anbau, Indoor 5-polige Anschlussbox mit Durchgangsverdrahtung 5 × 2,5 mm²	L1460 x W112 x H67
Zubehör				
 120006 45° Deckenhalterungen				L42 x W42 x H15
 820259 Einschaltstrombegrenzer DIN 16A				L90 x W18 x H58
 8249044900 Stahlseile 2x5m				L19 x W25 x H150