



Powerful in-ground luminaires for decorative and functional lighting of facades, gardens, patios, stairs and walls. Approved for 2000 kg load. Nemo II comes in symmetric versions with deep black reflectors for very low glare, and asymmetric versions that directs the light toward a facade or a wall. Nemo Siriak gives a decorative light along patios and facades.

Nemo II / Siriak



Produkt- und Umgebungsbilder



Artikel		Schutzklasse	Controller	Montage/Anschluss	Größe
	630070	Klasse I	Phasenabschnitt	Einbau, Indoor / Outdoor	Ø110 x H100
	Nemo II Mini 170lm 3000K Ra>80	IP67		Kabel 1m	
	Phasenabschnitt	IK10			
	4W LED				
	43 lm/W SDCM:3 L80/B20>50.000 Beam: 32°, Direkt, Linse				
	630071	Klasse I	Phasenabschnitt	Einbau, Indoor / Outdoor	Ø110 x H100
	Nemo II Mini Asymmetrisch 160lm	IP67		Kabel 1m	
	3000K Ra>80 Phasenabschnitt	IK10			
	4W LED				
	40 lm/W SDCM:3 L80/B20>50.000 Asymmetrisch, Linse				
	630072	Klasse I	Phasenabschnitt	Einbau, Indoor / Outdoor	Ø130 x H110
	Nemo II Midi 460lm 3000K Ra>80	IP67		Kabel 1m	
	Phasenabschnitt	IK10			
	9W LED				
	51 lm/W SDCM:3 L80/B20>50.000 Beam: 32°, Direkt, Linse				
	630073	Klasse I	Phasenabschnitt	Einbau, Indoor / Outdoor	Ø130 x H110
	Nemo II Midi Asymmetrisch 430lm	IP67		Kabel 1m	
	3000K Ra>80 Phasenabschnitt	IK10			
	9W LED				
	48 lm/W SDCM:3 L80/B20>50.000 Asymmetrisch, Linse				
	630075	Klasse I	Phasenabschnitt	Einbau, Indoor / Outdoor	Ø110 x H100
	Nemo Siriak 24lm 3000K Ra>80	IP67		Kabel 1m	
	Phasenabschnitt	IK10			
	4W LED				
	6 lm/W SDCM:3 L80/B20>50.000 Direkt, Linse				