LEDDim 350

LEDDim 350 with digital phase cut dimmer ensures stable dimming of the light even without connection N, which is optional. The dimmer automatically adapts to the light sources and ensures that the maximum light level is stable. It is possible to adjust light levels to the light sources by manually setting the minimum and maximum level. Switch the light on/off from two-way wall switch for multiple entrance points in corridors and staircases.

LEDDim 350

Produkt- und Umgebungsbilder

Artikelnummer

Artikel		Schutzklasse	Controller	Montage/Anschluss	Größe
	820481 **LEDDim Schwarz 350VA**	**IP20**	Phasenabschnitt	Einbau, Indoor	L84 x W84 x H42
	820470 **LEDDim Weiss 350VA**	**IP20**	Phasenabschnitt	Einbau, Indoor	L84 x W84 x H42
Zubehör					
	820417 **LEDDim 350/400/Smart Schwarz SG Front**				L83 x W83 x H29
	820330 **LEDDim Grau**			Indoor	L56 x W5 x H56
	820418 **LEDDim 350/400/Smart Silber Elko Adapter**				L55 x W55 x H12
	78500 **Aufputzgehäuse Weiss 1X**	**IP41**		Einbau, Indoor	L86 x W86 x H35
	820352 **LEDDim 350/400/Smart Weiss ABB Adapter**				L55 x W55 x H10
	820353 **LEDDim 350/400/Smart Weiss Schneider Adapter**				L56 x W56 x H12
	820424 **LEDDim 350/400/Smart Weiss SG Front**				L83 x W83 x H23