

Rax Soft 200 Connect Wireless



A version of Rax Soft 200, which is combined with a wide range of SG Connect Driver Kit Wireless to provide the desired amount of light. The lighting control is easy to configure using the SG Connect Commissioning App, and the luminaire can be used with a wireless sensor or as part of a larger system, along with other SG Connect luminaires with integrated sensors, which can easily be enlarged or reconfigured as needed. The light is turned on and off after a defined period of time, contributing to energy saving. Rax Soft Connect is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm.


Rax Soft 200 Connect Wireless



Produkt- und Umgebungsbilder



Artikel	Schutzklasse	Controller	Montage/Anschluss	Größe
 212772 Rax Soft 200 Satin 3000K Ra>80 Connect Wireless LED SDCM:2 L90/B10>100.000 Beam: 62°, Direkt, Satin Matt Reflector	Klasse II SELV IP44/IP20 IK08	Connect Wireless	Einbau, Indoor Quick connector	Ø216 x H93
 212773 Rax Soft 200 Satin 4000K Ra>80 Connect Wireless LED SDCM:2 L90/B10>100.000 Beam: 62°, Direkt, Satin Matt Reflector	Klasse II SELV IP44/IP20 IK08	Connect Wireless	Einbau, Indoor Quick connector	Ø216 x H93
Treiber				
 820503 Treiber kit Wireless 13W 300mA Connect 13W 100.000	Klasse II IP20	Connect	Einbau, Indoor 3 pol Linect / Anschlussklemme	L157 x W45 x H30
 820504 Treiber kit Wireless 18W 500mA Connect 18W 100.000	Klasse II IP20	Connect	Einbau, Indoor 3 pol Linect / Anschlussklemme	L157 x W45 x H30
 820506 Treiber kit Wireless 26W 700mA Connect 26W 100.000	Klasse II IP20	Connect	Einbau, Indoor 3 pol Linect / Anschlussklemme	L157 x W45 x H30
 820515 Treiber kit Wireless 35W 900mA Connect 35W 100.000	Klasse II IP20	Connect	Einbau, Indoor 3 pol Linect / Anschlussklemme	L157 x W45 x H30
Zubehör				

Artikel	Schutzklasse	Controller	Montage/Anschluss	Größe
				Ø270 x H16
				Ø300 x H16
				Ø218 x H12
				Ø220 x H12
				Ø218 x H12
				Ø218 x H12
				Ø270 x H16
				L585 x W260 x H15