



Design: F Mark Recessed or surface-mounted using accessories, low profile 35 mm height, direct LED luminaire, 592x592 mm for mounting in visible T-rail ceilings or 599x599 mm for concealed ceiling systems. With unique energy efficiency (up to 112 lm/W), collimated TIR optics with angled illuminated edge made of sheet steel. Precise low unified glare rating (UGR)

Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 8246093705 Molior Line 592x592 Blanc 1520lm 3000K Ra>80 14W LED 109 lm/W SDCM:3 L90/B10>50,000 Directe, Lentille R transparente	Classe III IP20		Encastré, Indoor	L592 x W592 x H35
 8246093718 Molior Line 592x592 Blanc 1580lm 4000K Ra>80 14W LED 113 lm/W SDCM:3 L90/B10>50,000 Directe, Lentille R transparente	Classe III IP20		Encastré, Indoor	L592 x W592 x H35
Alimentation				
 820083 Sense Driver Blanc 3000lm 25W 700mA DALI-2 / Push Dim 25W 100,000	Classe II IP20	DALI-2 / Push Dim	Encastré, Indoor Linect 5 pôles / bornier sans vis	L124 x W79 x H22
 8246093158 Molior Line 1 Line / 1 Corner 14W 300mA Non dimmable				
 8246093815 Molior Line 2 Line / 4 Corner 36W 700mA Non dimmable				L125 x H35
Accessoires				
 8249045006 Sense 600x600 Blanc Plaque de plâtre/Troldtekt Encadrement encastré				L640 x W640 x H40
 8246094364 Boîtier d'éclairage de secours On-Off/Coupure de phase / EM Selvtest, Secours 3 heures				L270 x W75 x H35
 8246094500 Boîtier d'éclairage de secours Driver DALI / EM DALI/Self test, Secours 3 heures				L270 x W75 x H35