

Curve Direct



Round, attractive wall luminaire for horizontal/vertical installation and indoors/outdoors. Made of die-cast powder-coated aluminium. Glass diffuser. Can be mounted as a downlight or as an uplight, IP65, integrated LED, mounting back panel with two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. IP65 and vandal-resistant rating IK06.

Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 611396 Curve Direct Noir 530lm 2700K Ra>80 Coupure de phase 7W LED 76 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Directe, Verre dépoli	Classe I IP65 IK06	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	W320 x H60 x D103
 611398 Curve Direct Graphite 530lm 2700K Ra>80 Coupure de phase 7W LED 76 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Directe, Verre dépoli	Classe I IP65 IK06	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	W320 x H60 x D103
 611394 Curve Direct Blanc 530lm 2700K Ra>80 Coupure de phase 7W LED 76 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Directe, Verre dépoli	Classe I IP65 IK06	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	W320 x H60 x D103
 611397 Curve Direct Noir 550lm 3000K Ra>80 Coupure de phase 7W LED 79 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Directe, Verre dépoli	Classe I IP65 IK06	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	W320 x H60 x D103
 611399 Curve Direct Graphite 550lm 3000K Ra>80 Coupure de phase 7W LED 79 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Directe, Verre dépoli	Classe I IP65 IK06	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	W320 x H60 x D103
 611395 Curve Direct Blanc 550lm 3000K Ra>80 Coupure de phase 7W LED 79 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Directe, Verre dépoli	Classe I IP65 IK06	Coupure de phase	Surface, Indoor / Outdoor Bornier sans vis	W320 x H60 x D103