



Farm 66 is a very hardy luminaire, especially suitable for pig farms and the like. The LED compartment has an extra high protection rating to withstand ammonia gasses in such environments. The luminaire housing is made of hard UV-stabilised and anti-chemical coated polycarbonate. The coating is resistant to ammonia, washing detergents* etc, and makes it suitable also for car wash halls and similar. It is easy to install by just snapping into mounting clips and using the unique one-hand closing mechanism at both ends. The looping options with double cable gland in each end and through wiring gives full flexibility for larger installations. * Farm 66 is resistant to aqueous salt solutions up to about 60°C and diluted acids. It has limited resistance to alcohols, aliphatic hydrocarbons, and diluted alkalis, and is not resistant to concentrated mineral acids and alkalis, ammonia, amines, aromatic and/or halogenated hydrocarbons, esters, ethers, ketones, or solvents such as methyl ethylketone, tetrahydrofuran, toluene, and dimethyl-formamide.

Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 120012 Farm 66 1500 Gris 5860lm 4000K Ra>80 DALI-2 / Push Dim 43W LED 136 lm/W SDCM:3 L90/B50>50,000 Directe, Opale	Classe I IP66 IK08	DALI-2 / Push Dim	Surface, Indoor Bornier sans vis à 7 pôles avec câblage traversant 5 x 2,5 mm ² (+ DALI)	L1460 x W112 x H67
 120014 Farm 66 Pro 1500 Gris 9820lm 4000K Ra>80 DALI-2 / Push Dim 65W LED 151 lm/W SDCM:3 L80/B10>100,000 Directe, Opale	Classe I IP66 IK08	DALI-2 / Push Dim	Surface, Indoor Bornier sans vis à 7 pôles avec câblage traversant 5 x 2,5 mm ² (+ DALI)	L1460 x W112 x H67
 120009 Farm 66 1200 Gris 4030lm 4000K Ra>80 Non dimmable 34W LED 119 lm/W SDCM:3 L90/B50>50,000 Directe, Opale	Classe I IP66 IK08	Non dimmable	Surface, Indoor Bornier sans vis à 5 pôles avec câblage traversant 5 x 2,5 mm ²	L1174 x W112 x H67
 120010 Farm 66 1500 Gris 5720lm 4000K Ra>80 Non dimmable 47W LED 122 lm/W SDCM:3 L90/B50>50,000 Directe, Opale	Classe I IP66 IK08	Non dimmable	Surface, Indoor Bornier sans vis à 5 pôles avec câblage traversant 5 x 2,5 mm ²	L1460 x W112 x H67
Accessoires				
 120006 45° Supports de plafond				L42 x W42 x H15
 820259 Limiteur de courant d'appel DIN 16A				L90 x W18 x H58
 8249044900 Kit suspension 2x5m				L19 x W25 x H150