



Powerful in-ground luminaires for decorative and functional lighting of facades, gardens, patios, stairs and walls. Approved for 2000 kg load. Nemo II comes in symmetric versions with deep black reflectors for very low glare, and asymmetric versions that directs the light toward a facade or a wall. Nemo Siriak gives a decorative light along patios and facades.

Nemo II / Siriak



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 630070 Nemo II Mini 170lm 3000K Ra>80 Coupure de phase 4W LED 43 lm/W SDCM:3 L80/B20>50,000 Beam: 32°, Directe, Lentille	Classe I IP67 IK10	Coupure de phase	Encastré, Indoor / Outdoor Câble 1m	Ø110 x H100
 630071 Nemo II Mini Asymétrique 160lm 3000K Ra>80 Coupure de phase 4W LED 40 lm/W SDCM:3 L80/B20>50,000 Directe, Lentille	Classe I IP67 IK10	Coupure de phase	Encastré, Indoor / Outdoor Câble 1m	Ø110 x H100
 630072 Nemo II Midi 460lm 3000K Ra>80 Coupure de phase 9W LED 51 lm/W SDCM:3 L80/B20>50,000 Beam: 32°, Directe, Lentille	Classe I IP67 IK10	Coupure de phase	Encastré, Indoor / Outdoor Câble 1m	Ø130 x H110
 630073 Nemo II Midi Asymétrique 430lm 3000K Ra>80 Coupure de phase 9W LED 48 lm/W SDCM:3 L80/B20>50,000 Directe, Lentille	Classe I IP67 IK10	Coupure de phase	Encastré, Indoor / Outdoor Câble 1m	Ø130 x H110
 630075 Nemo Siriak 24lm 3000K Ra>80 Coupure de phase 4W LED 6 lm/W SDCM:3 L80/B20>50,000 Directe, Lentille	Classe I IP67 IK10	Coupure de phase	Encastré, Indoor / Outdoor Câble 1m	Ø110 x H100