

Sense IP65 Eco



Sense IP65 Eco is a waterproof luminaire with opal prismatic front, delivered complete with driver. Ideal for industrial kitchens, hospitals, laboratories, and production facilities. Very low glare, UGR

Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212468 Sense IP65 Eco Blanc 4060lm 3000K Ra>80 DALI-2 34W LED 119 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Directe, Opalprism	Classe II IP65	DALI-2	Encastré, Indoor Linect 5 pôles / bornier sans vis	L597 x W597 x H53
 212390 Sense IP65 Eco Blanc 4060lm 3000K Ra>80 Coupure de phase 34W LED 119 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Directe, Opalprism	Classe II IP65	Coupure de phase	Encastré, Indoor	L597 x W597 x H53
 212414 Sense IP65 Eco Blanc 4350lm 4000K Ra>80 DALI-2 34W LED 128 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Directe, Opalprism	Classe II IP65	DALI-2	Encastré, Indoor Linect 5 pôles / bornier sans vis	L597 x W597 x H53
 212391 Sense IP65 Eco Blanc 4350lm 4000K Ra>80 Coupure de phase 34W LED 128 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Directe, Opalprism	Classe II IP65	Coupure de phase	Encastré, Indoor	L597 x W597 x H53
Accessoires				
 820489 Sensor Dim Box Blanc 200VA				L220 x W75 x H34
 8249045006 Sense 600x600 Blanc Plaque de plâtre/Troldtekt Encadrement encastré				L640 x W640 x H40
 8246094364 Boîtier d'éclairage de secours On-Off/Coupure de phase / EM Self test, Secours 3 heures				L270 x W75 x H35
 8246094500 Boîtier d'éclairage de secours Alim. DALI / EM DALI/Self test, Secours 3 heures				L270 x W75 x H35