











StripLine is a flexible LED strip system designed to provide architectural lighting on ceilings and walls, in niches and cabinets, and is suitable for both indoor and outdoor use. StripLine RGBW allows you to create all the colours of the rainbow by mixing red, green and blue (RGB) in different ways. It also features pure white (W). StripLine RGBW requires a driver and controller in order to operate correctly. To control the controller (the light), you can use a handy remote control and/or pulse switch. The LED strip is encapsulated to an IP54 rating, and is supplied with mounting tape on the rear and connection cables already fully fitted. The LED strip must be fitted in one of the available StripLine aluminium profiles for surface-mounted, corner, recessed or frameless installations. It can also be used independently in indoor settings. The profiles are supplied with a solid polycarbonate front diffuser that can be easily attached and removed. The front diffuser is also supplied as a roll, providing the option of very long, continuous fronts. (The diffuser on roll and the Round Diffuser are not compatible with the Slim and Soft profiles). Different driver kits are available, dimmable with phase-cut or push dim. Driver kits come complete with screwless terminal block for looping. The drivers are encapsulated to an IP20 rating. StripLine RGBW can be cut at intervals of 7.1 cm to be tailored to each individual installation. When cutting, silicone should be applied to maintain water protection.

StripLine RGBW



Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 <p>391452 StripLine 5m 790lm/m RGBW (3000K) Ra>90 LED SDCM:3 L70/B50>50,000 Beam: 120°, Directe,</p>	Classe III IP54		Surface, Indoor / Outdoor Câble 2x2m	L5000 x W12 x H3.2
 <p>391479 StripLine 10m 790lm/m RGBW (3000K) Ra>90 LED SDCM:3 L70/B50>50,000 Beam: 120°, Directe,</p>	Classe III IP54		Surface, Indoor / Outdoor Câble 2x2m	L10000 x W12 x H3.2
Alimentation				
 <p>820440 SG Blanc Driver 24V 36W Coupure de phase</p>				L200 x W85 x H35
 <p>820441 SG Blanc Driver 24V 75W Coupure de phase</p>				L200 x W85 x H35
 <p>820442 SG Blanc Driver 24V 150W Coupure de phase</p>				L310 x W85 x H35
Accessoires				
 <p>391457 Remote Control Noir RF RGBW</p>				L139 x W36 x H11
 <p>391455 Controller Blanc RF RGBW Télécommande RF / Push Dim</p>				L175 x W45 x H27
 <p>820483 LEDDim Smart Color Controller Blanc SG Smart/ Télécommande RF * / Push Dim</p>				L175 x W45 x H27