



EcoLine is a slim and stylish ceiling luminaire suitable for use in offices, schools and public buildings. Designed for quick and easy installation. Three-layer optical system with low glare: UGR

Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212802 EcoLine 1600 Blanc 4880lm 3000K Ra>80 DALI-2 36W LED 136 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Directe, Opalprism	Classe I IP20	DALI-2	Suspendu ou surface, Indoor Bornier sans vis 3+2 pôles	L1600 x W166 x H47
 212093 EcoLine 1200 Blanc 3910lm 3000K Ra>80 DALI-2 / Push Dim 30W LED 130 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Directe, Opalprism	Classe I IP20	DALI-2 / Push Dim	Suspendu ou surface, Indoor Bornier sans vis 3+2 pôles	L1235 x W166 x H47
 212091 EcoLine 1200 Blanc 3910lm 3000K Ra>80 Non dimmable 30W LED 130 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Directe, Opalprism	Classe I IP20	Non dimmable	Suspendu ou surface, Indoor Bornier sans vis 3 pôles	L1235 x W166 x H47
 212800 EcoLine 1600 Blanc 4880lm 3000K Ra>80 Non dimmable 36W LED 136 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Directe, Opalprism	Classe I IP20	Non dimmable	Suspendu ou surface, Indoor Bornier sans vis 3 pôles	L1600 x W166 x H47
 212803 EcoLine 1600 Blanc 5180lm 4000K Ra>80 DALI-2 36W LED 144 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Directe, Opalprism	Classe I IP20	DALI-2	Suspendu ou surface, Indoor Bornier sans vis 3+2 pôles	L1600 x W166 x H47
 212094 EcoLine 1200 Blanc 4150lm 4000K Ra>80 DALI-2 / Push Dim 30W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Directe, Opalprism	Classe I IP20	DALI-2 / Push Dim	Suspendu ou surface, Indoor Bornier sans vis 3+2 pôles	L1235 x W166 x H47

Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212092 EcoLine 1200 Blanc 4150lm 4000K Ra>80 Non dimmable 30W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Directe, Opalprism	Classe I IP20	Non dimmable	Suspendu ou surface, Indoor Bornier sans vis 3 pôles	L1235 x W166 x H47
 212801 EcoLine 1600 Blanc 5180lm 4000K Ra>80 Non dimmable 36W LED 144 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Directe, Opalprism	Classe I IP20	Non dimmable	Suspendu ou surface, Indoor Bornier sans vis 3 pôles	L1600 x W166 x H47
Accessoires				
 212255 T-profil Blanc Rail de suspension 600mm				L596 x W35 x H17
 212095 EcoLine Kit suspension				L2000