

Sense Line



Create your own design in T-profile ceilings with Sense Line 600. Sense Line is also available in 1200mm length. The luminaire has a light steel housing and a 3-layer optical system for low glare with UGR

Galerie de produits et d'environnements



Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212691 Sense Line 120x600 Blanc Linect 1160lm 3000K Ra>80 DALI-2 10W LED 116 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Directe, Opalprism	Classe II SELV IP20	DALI-2	Encastré, Indoor Linect 5 pôles / bornier sans vis	L595 x W118 x H35
 212695 Sense Line 120x1200 Blanc Linect 2310lm 3000K Ra>80 DALI-2 19W LED 122 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Directe, Opalprism	Classe II SELV IP20	DALI-2	Encastré, Indoor Linect 5 pôles / bornier sans vis	L1195 x W118 x H35
 212690 Sense Line 120x600 Blanc Linect 1160lm 3000K Ra>80 Coupure de phase 9W LED 129 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Directe, Opalprism	Classe II SELV IP20	Coupure de phase	Encastré, Indoor Linect 3 pôles / bornier sans vis	L595 x W118 x H35
 212694 Sense Line 120x1200 Blanc Linect 2310lm 3000K Ra>80 Coupure de phase 18W LED 128 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Directe, Opalprism	Classe II SELV IP20	Coupure de phase	Encastré, Indoor Linect 3 pôles / bornier sans vis	L1195 x W118 x H35
 212693 Sense Line 120x600 Blanc Linect 1230lm 4000K Ra>80 DALI-2 10W LED 123 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Directe, Opalprism	Classe II SELV IP20	DALI-2	Encastré, Indoor Linect 5 pôles / bornier sans vis	L595 x W118 x H35
 212697 Sense Line 120x1200 Blanc Linect 2460lm 4000K Ra>80 DALI-2 19W LED 129 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Directe, Opalprism	Classe II SELV IP20	DALI-2	Encastré, Indoor Linect 5 pôles / bornier sans vis	L1195 x W118 x H35

Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 212692 Sense Line 120x600 Blanc Linect 1230lm 4000K Ra>80 Coupure de phase 9W LED 137 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Directe, Opalprism	Classe II SELV IP20	Coupure de phase	Encastré, Indoor Linect 3 pôles / bornier sans vis	L595 x W118 x H35
 212696 Sense Line 120x1200 Blanc Linect 2460lm 4000K Ra>80 Coupure de phase 18W LED 137 lm/W SDCM:3 L80/B20>100,000 Beam: 84°, Directe, Opalprism	Classe II SELV IP20	Coupure de phase	Encastré, Indoor Linect 3 pôles / bornier sans vis	L1195 x W118 x H35
Accessoires				
 820489 Sensor Dim Box Blanc 200VA				L220 x W75 x H34
 212698 Sense Line Ressorts de fixation				L64 x W31 x H21
 8246094364 Boîtier d'éclairage de secours On-Off/Coupure de phase / EM Selvtest, Secours 3 heures				L270 x W75 x H35
 8246094500 Boîtier d'éclairage de secours Alim. DALI / EM DALI/Self test, Secours 3 heures				L270 x W75 x H35