

Disc 480 D/I



Disc 480 D/I is an energy efficient and stylish surface-mounted luminaire with a slim profile, providing any room with a modern and refined look. Opal prismatic diffuser ensures glare-free and comfortable lighting with a decorative indirect light. It is possible to choose between 3000K/4000K with the connection cable. Disc 480 D/I is produced in durable aluminium and polycarbonate. Installation is simple, thanks to the quick connection between the luminaire and the backplate, which can be mounted directly onto all standard ceiling boxes. Visible cabling also possible.

Disc 480 D/I



Galerie de produits et d'environnements



Article		Protection	Convertisseurs	Montage/Connexion	Dimensions
	606201 Disc 480 Noir D/I 3940lm 2700K Ra>80 Coupure de phase 34W LED 116 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Directe, Opalprism	Classe II IP20 IK10	Coupure de phase	Surface, Indoor Bornier sans vis	Ø467 x H62
	606200 Disc 480 Blanc D/I 4220lm 2700K Ra>80 Coupure de phase 34W LED 124 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Directe, Opalprism	Classe II IP20 IK10	Coupure de phase	Surface, Indoor Bornier sans vis	Ø467 x H62
	606205 Disc 480 Noir D/I 4000/4270lm 3000/4000K Ra>80 DALI-2 / Push Dim 34W LED 118 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Directe, Opalprism	Classe II IP20 IK10	DALI-2 / Push Dim	Surface, Indoor Bornier sans vis	Ø467 x H62
	606209 Disc 480 Noir D/I 4000/4270lm 3000/4000K Ra>80 Sensor Dim 34W LED 118 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Directe, Opalprism	Classe II IP20 IK10	Sensor Dim	Surface, Indoor Bornier sans vis	Ø467 x H62
	606182 Disc 480 Noir D/I 4000/4270lm 3000/4000K Ra>80 Coupure de phase 34W LED 118/126 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Directe, Opalprism	Classe II IP20 IK10	Coupure de phase	Surface, Indoor Bornier sans vis	Ø467 x H62
	606204 Disc 480 Blanc D/I 4160/4420lm 3000/4000K Ra>80 DALI-2 / Push Dim 34W LED 122 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Directe, Opalprism	Classe II IP20 IK10	DALI-2 / Push Dim	Surface, Indoor Bornier sans vis	Ø467 x H62

Article	Protection	Convertisseurs	Montage/Connexion	Dimensions
 606208 Disc 480 Blanc D/I 4160/4420lm 3000/4000K Ra>80 Sensor Dim 34W LED 122 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Directe, Opalprism	Classe II IP20 IK10	Sensor Dim	Surface, Indoor Bornier sans vis	Ø467 x H62
 606180 Disc 480 Blanc D/I 4160/4420lm 3000/4000K Ra>80 Coupure de phase 34W LED 122/130 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Directe, Opalprism	Classe II IP20 IK10	Coupure de phase	Surface, Indoor Bornier sans vis	Ø467 x H62
Accessoires				
 606095 Disc/Frosta Noir Suspension Adaptateur				L5000 x W102 x H22
 606094 Disc/Frosta Blanc Suspension Adaptateur				L5000 x W102 x H22