

CE – Declaration of Conformity

CE-UKCA241204H Sense 600x600 Round Document:

Product Inspection: PI241203A RA241007A Risk Assessment:

We, **SG Armaturen AS**

Skytterheia 25

N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire

Type

Sense 600x600 Round

Name(s)

To which this declaration relates is in conformity with the following EC-directive(s):

Directive 2014 / 30 / EU Directive 2014 / 35 / EU Directive 2009 / 125 / EF (Regs 244/2009, 245/2009, 347/2010)* Electromagnetic compatibility (EMC) Low Voltage directive (LVD) Ecodesign requirements (ECO) * As applicable and including amendments

RoHS 2011 / 65 / EU + RoHS III / EU 2015/863

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022 (Luminaires - General requirements)

EN 60598-2-2:2012 (Luminaires - Recessed)

EN 60598-2-22:2014 (Luminaires – emergency lighting)

EN 62471:2008

(Luminaires – Photobiological safety of lamps and lamp systems)

EN 62493:2015 (EMF – Lighting equipment related to human exposure)

EN 55015:2019+A11:2020 (EMC - Radio disturbance)

EN 61000-3-2:2019 (EMC - Harmonics)

EN 61000-3-3:2013+A1:2019 (EMC - Voltage change, fluctuation & flicker)

EN 61547:2009 (EMC - Immunity)

CE declaration date: 2024

issued by SG Armaturen AS Statement of Conformity

Manufacturer Lillesand, 04/12-2024 Place and date of issue

Martin Ettrup Approval Engineer Name of authorized person



UKCA – Declaration of Conformity

Document: CE-UKCA241204H Sense 600x600 Round

Product Inspection: PI241203A Risk Assessment: RA241007A

We, SG Armaturen AS

Skytterheia 25

N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire

Туре

Sense 600x600 Round

Name(s)

To which this declaration relates is in conformity with the following UK-regulations:

UK SI 2016 No. 1091	UK SI 2016 No. 1101	UK SI 2010 No. 2617	UK SI 2012 No. 3032
The Electromagnetic Compatibility Regulations 2010	The Electrical Equipment (Safety) Regulations 2016	The Ecodesign for Energy-Related Products Regulations 2010 Equipment (Safety) Regulations 2016	The Restriction of the Use of Certain Hazardous Substances in Electrical Equipment Regulations 2012

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022 (Luminaires - General requirements)

EN 60598-2-2:2012 (Luminaires - Recessed)

EN 60598-2-22:2014 (Luminaires – emergency lighting)

EN 62471:2008 (Luminaires – Photobiological safety of lamps and lamp systems)

EN 62493:2015 (EMF – Lighting equipment related to human exposure)

EN 55015:2019+A11:2020 (EMC - Radio disturbance)

EN 61000-3-2:2019 (EMC - Harmonics)

EN 61000-3-3:2013+A1:2019 (EMC – Voltage change, fluctuation & flicker)

EN 61547:2009 (EMC - Immunity)

UK SI 2021 No. 1095 (Luminaires – The Ecodesign for Energy-Related products

and Energy Information)

UKCA declaration date: 2024

Statement of Conformity issued by SG Armaturen AS

ManufacturerMartin EttrupLillesand, 04/12-2024Approval EngineerPlace and date of issueName of authorized person

Signature of authorized person



Declaration of Conformity statements/valid for the following products:

Product ID Number	Product Description	Article type	Article group
7021982126741 7021982126758	Sense Pro Round 600x600 White Sense Pro Round 600x600 White	3000K Ra>80 4000K Ra>80	701567 701567
Drivers			
7021988204085 7021988204924 7021988204047 7021988204900 7021988204917 7021988204078 7021988202739 7021988200834 7021988204931 7021988204948	Sense Driver White	5000lm 38W 1050mA Trailing edge dimming 4000lm 32W 900mA Trailing edge dimming 4000lm 33W 900mA DALI / Push Dim 3000lm 26W 700mA Trailing edge dimming 3000lm 26W 700mA Trailing edge dimming / Linect 5000lm 40W 1050mA DALI / Push Dim Driver 700mA DALI 3000lm 26W 700mA DALI / Push Dim 4000lm 32W 900mA Trailing edge dimming / Linect 5000lm 38W 1050mA Trailing edge dimming	
Emergencybox			
5703821177344 5703821177276 5703821177504	Emergencybox Driver Emergencybox Emergencybox Driver	DALI / EM Emergency 3 hours DALI On-Off/Trailing edge / EM Self test, DALI / EM DALI/Self test, Emergence	Emergency 3 hours