

Callisto Wall



Good little LED luminaire for walls and ceiling. For both outdoor and indoor use. Well integrated LED chip, dimmable via phase-dimming. Made of die-cast powder-coated aluminium, glass diffuser. 33 cm in total height, KL II means that it can be mounted without earthing, direct 230 V with loopable quick clips.

Callisto Wall



Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 914017 Callisto Wall Zwart 100lm 2700K Ra>80 Fase afsnijding 3W LED 33 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetrisch, Helder glas	Klasse II IP65 IK06	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	Ø110 x H35
 923017 Callisto Wall Grafiet 100lm 2700K Ra>80 Fase afsnijding 3W LED 33 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetrisch, Helder glas	Klasse II IP65 IK06	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	Ø110 x H35
 912017 Callisto Wall Wit 110lm 2700K Ra>80 Fase afsnijding 3W LED 37 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetrisch, Helder glas	Klasse II IP65 IK06	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	Ø110 x H35
 914015 Callisto Wall Zwart 110lm 3000K Ra>80 Fase afsnijding 3W LED 37 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetrisch, Helder glas	Klasse II IP65 IK06	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	Ø110 x H35
 923015 Callisto Wall Grafiet 110lm 3000K Ra>80 Fase afsnijding 3W LED 37 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetrisch, Helder glas	Klasse II IP65 IK06	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	Ø110 x H35

Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
		r		
		Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	Ø110 x H35
912015 Callisto Wall Wit 120lm 3000K Ra>80 Fase afsnijding 3W LED 40 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetrisch, Helder glas	Klasse II IP65 IK06			
				
		Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	Ø110 x D35
914016 Callisto Wall Zwart 120lm 4000K Ra>80 Fase afsnijding 3W LED 40 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetrisch, Helder glas	Klasse II IP65 IK06			
				
		Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	Ø110 x H35
923016 Callisto Wall Grafiet 110lm 4000K Ra>80 Fase afsnijding 3W LED 37 lm/W SDCM:3 L70/B50>50,000 Beam: 70°/40°, Direct/Asymmetrisch, Helder glas	Klasse II IP65 IK06			