

Curve Direct



Round, attractive wall luminaire for horizontal/vertical installation and indoors/outdoors. Made of die-cast powder-coated aluminium. Glass diffuser. Can be mounted as a downlight or as an uplight, IP65, integrated LED, mounting back panel with two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. IP65 and vandal-resistant rating IK06.

Curve Direct



Product- en omgevingsbeelden



Artikel		Bescherming	Regelapparaatuu r	Montage/Aansluiting	Afmetingen
	611396	Klasse I	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	W320 x H60 x D103
	Curve Direct Zwart 530lm 2700K Ra>80 Fase afsnijding 7W LED 76 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Mat glas	IP65 IK06			
	611398	Klasse I	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	W320 x H60 x D103
	Curve Direct Grafiet 530lm 2700K Ra>80 Fase afsnijding 7W LED 76 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Mat glas	IP65 IK06			
	611394	Klasse I	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	W320 x H60 x D103
	Curve Direct Wit 530lm 2700K Ra>80 Fase afsnijding 7W LED 76 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Mat glas	IP65 IK06			
	611397	Klasse I	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	W320 x H60 x D103
	Curve Direct Zwart 550lm 3000K Ra>80 Fase afsnijding 7W LED 79 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Mat glas	IP65 IK06			
	611399	Klasse I	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	W320 x H60 x D103
	Curve Direct Grafiet 550lm 3000K Ra>80 Fase afsnijding 7W LED 79 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Mat glas	IP65 IK06			
	611395	Klasse I	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	W320 x H60 x D103
	Curve Direct Wit 550lm 3000K Ra>80 Fase afsnijding 7W LED 79 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Mat glas	IP65 IK06			