

Cube DimToWarm



Attractive downlight for indoor or outdoor use under eaves, 30-degree 360-degree stepless tilt. Mounted directly on ceiling or on known ceiling electrical boxes. Well integrated LED chip with DimToWarm 2800K-2000K via phase-dimming. Made of die-cast powder-coated aluminium, glass diffuser. 42-degree beam angle via reflector. Quick connection between luminaire body and ceiling mounting plate. Luminaire body is snapped into place and secured using two concealed internal screws.

Cube DimToWarm



Product- en omgevingsbeelden





Artikel	Bescherming	Regelapparaatuu r	Montage/Aansluiting	Afmetingen
 906213 Cube DimToWarm Zwart DimToWarm 490lm 2000-2800K Ra>95 Fase afsnijding 7.3W LED 67 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Klasse I IP21	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	L132 x W132 x H65
 906233 Cube DimToWarm Zwart DimToWarm 980lm 2000-2800K Ra>95 Fase afsnijding 14.8W LED 66 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Klasse I IP21	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	L231 x W132 x H65
 906211 Cube Wit DimToWarm 550lm 2000-2800K Ra>95 Fase afsnijding 7.3W LED 75 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Klasse I IP21	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	L132 x W132 x H65
 906231 Cube Wit DimToWarm 1100lm 2000-2800K Ra>95 Fase afsnijding 14.8W LED 74 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Klasse I IP21	Fase afsnijding	Opbouw, Indoor / Outdoor Schroefloos klemmenblok	L231 x W132 x H65