



Attractive downlight for indoor use with 30-degree 360-degree stepless tilt. Well integrated LED chip with DimToWarm 2800K–2000K via phase-dimming or DALI driver. Made of die-cast powder-coated aluminium or brushed steel, glass diffuser. 42-degree scattering angle via reflector. Low surface-mounted, Ø83 hole dimensions. Tool-free mounting in mounting box for direct 230 V with loopable quick clips and automatic strain relief. IP44, KL III with dedicated circuit.

Junistar DimToWarm





Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	902236	Klasse II SELV	Fase afsnijding	Ø94 x H50
	Junistar DimToWarm Zwart/Goud 490lm 2000-2800K Ra>95 Fase afsnijding 8W LED 61 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	IP44	Schroefloos klemmenblok	
	901241	Klasse II SELV	DALI-2	Ø94 x H50
	Junistar DimToWarm Wit 560lm 2000-2800K Ra>95 DALI-2 8W LED 70 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	IP44	Schroefloos klemmenblok	
Accessoires				
	9143			Ø133 x L133 x W133 x H4
	Rehab Ring Zwart 133mm voor Junistar, Uniled, Soft & Jupiter			
	9236			Ø180 x H45
	Rehab Ring Zwart 180mm voor Junistar, Uniled, Soft & Jupiter			
	9973			Ø133 x H4
	Rehab Ring Geborsteld Staal 133mm voor Junistar, Uniled, Soft & Jupiter			
	9223			Ø133 x L133 x W133 x H4
	Rehab Ring Wit 133mm voor Junistar, Uniled, Soft & Jupiter			
	9224			Ø180 x H45
	Rehab Ring Wit 180mm voor Junistar, Uniled, Soft & Jupiter			
	9227			Ø250 x H45
	Rehab Ring Wit 250mm voor Junistar, Uniled, Soft & Jupiter			
	820090			L250 x W13 x H13
	Noodbox Adapter kit voor downlight			



Artikel	Bescherming	Regelapparaatuu r	Montage/Aansluiting	Afmetingen
 8246094364 Noodbox On-Off/Fase afsnijding / EM Self test, Nood 3h				L270 x W75 x H35
 8246094500 Noodbox Driver DALI / EM DALI/Self test, Nood 3h				L270 x W75 x H35