



Junistar IsoSafe TW is an attractive downlight for indoor use with 30° 360° stepless tilt. Our IsoSafe products can be mounted directly in insulation (IsoSafe). Junistar IsoSafe TW is equipped with the revolutionary Tunable White (TW) LEDDim technology. You can regulate both the lighting level and colour without extra cabling, using SG's TW LEDDim Smart dimmer. Control it manually or via the LEDDim app. When using the SG Smart Gateway, you can also set a daylight sequence which changes colour and intensity throughout the day. You can choose a standard rhythm or set your own. Junistar IsoSafe TW comes in two colour temperature ranges: 2700-6500K for traditional TW with the typical circadian spectrum, or 2000-4000K for typical residential use including warm and cosy colour temperatures. This is similar to DimToWarm, but with independent control of light level and colour temperature. Made of die-cast, powder-coated aluminium or brushed steel with glass diffuser. Tool-free mounting in mounting box for direct 230 V with loopable quick clips, automatic strain relief and Linect.

Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	912245	Klasse II SELV	TW LEDDim	Ø94
	Junistar IsoSafe TW Zwart 460lm	IP44/IP20	Inbouw, Indoor	Schroefloos klemmenblok
	(@4000K) 2000-4000K Ra>90 TW			
	LEDDim			
	8.5W LED			
	54 lm/W SDCM:2			
	L90/B10>100,000			
	Beam: 42°, Direct, Reflector			
	912243	Klasse II SELV	TW LEDDim	Ø94
	Junistar IsoSafe TW Wit 500lm	IP44/IP20	Inbouw, Indoor	Schroefloos klemmenblok
	(@4000K) 2000-4000K Ra>90 TW			
	LEDDim			
	8.5W LED			
	59 lm/W SDCM:2			
	L90/B10>100,000			
	Beam: 42°, Direct, Reflector			
	912244	Klasse II SELV	TW LEDDim	Ø94
	Junistar IsoSafe TW Zwart 500lm	IP44/IP20	Inbouw, Indoor	Schroefloos klemmenblok
	(@6500K) 2700-6500K Ra>90 TW			
	LEDDim			
	8.5W LED			
	59 lm/W SDCM:2			
	L90/B10>100,000			
	Beam: 42°, Direct, Reflector			
	912242	Klasse II SELV	TW LEDDim	Ø94
	Junistar IsoSafe TW Wit 530lm	IP44/IP20	Inbouw, Indoor	Schroefloos klemmenblok
	(@6500K) 2700-6500K Ra>90 TW			
	LEDDim			
	8.5W LED			
	62 lm/W SDCM:2			
	L90/B10>100,000			
	Beam: 42°, Direct, Reflector			
Accessoires				
	9143			Ø133 x L133 x W133 x H4
	Rehab Ring Zwart 133mm voor Junistar, Uniled, Soft & Jupiter			
	9236			Ø180 x H45
	Rehab Ring Zwart 180mm voor Junistar, Uniled, Soft & Jupiter			



Artikel	Bescherming	Regelapparatuu	Montage/Aansluiting	Afmetingen
	9223 Rehab Ring Wit 133mm voor Junistar, Uniled, Soft & Jupiter	r		Ø133 x L133 x W133 x H4
	9224 Rehab Ring Wit 180mm voor Junistar, Uniled, Soft & Jupiter			Ø180 x H45
	9227 Rehab Ring Wit 250mm voor Junistar, Uniled, Soft & Jupiter			Ø250 x H45