

Tube Micro R



Tube Micro R is a stylish, minimalist built-in spot for installation in level or sloping ceilings. Its intense light can be used indirectly for general lighting or directly to highlight parts of the surroundings. The spot can be turned and tilted to direct the light to exactly where light is needed. Tube Micro R can be installed easily in holes in the ceiling using springs. The luminaire is ideal for refurbishments, as it fits in holes from Ø68–83 mm. The luminaire also fits SG's Rehabrings (accessory) up to Ø250. The driver and junction box are IsoSafe and can be installed directly into insulation. Can be looped and is Class II, which facilitates easy replacement where there is no earth lead. Tube Micro R comes as standard with a low-glare black bezel. Other bezels are available separately as accessories.

Tube Micro R



Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 320755 Tube Micro R Zwart DimToWarm 590lm 2000-2800K Ra>95 DALI-2 12W LED 49 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	DALI-2	Inbouw, Indoor	L135 x W39 x H135
 320712 Tube Micro R Zwart DimToWarm 590lm 2000-2800K Ra>95 Fase afsnijding 12W LED 49 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	Fase afsnijding	Inbouw, Indoor	L135 x W39 x H135
 320860 Tube Micro R Messing DimToWarm 590lm 2000-2800K Ra>95 Fase afsnijding 12W LED 49 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	Fase afsnijding	Inbouw, Indoor	L135 x W39 x H135
 320752 Tube Micro R Wit DimToWarm 590lm 2000-2800K Ra>95 DALI-2 12W LED 49 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	DALI-2	Inbouw, Indoor	L135 x W39 x H135
 320709 Tube Micro R Wit DimToWarm 590lm 2000-2800K Ra>95 Fase afsnijding 12W LED 49 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	Fase afsnijding	Inbouw, Indoor	L135 x W39 x H135
 320753 Tube Micro R Zwart 680lm 2700K Ra 98 DALI-2 15W LED 45 lm/W SDCM:2 L90/B10>100,000	Klasse II IP20	DALI-2	Inbouw, Indoor	L135 x W39 x H135

Artikel	Beam: 36°, Direct, Reflector	Bescherming	Regelapparaatuu r	Montage/Aansluiting	Afmetingen
	320710 Tube Micro R Zwart 680lm 2700K Ra 98 Fase afsnijding 15W LED 45 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	Fase afsnijding	Inbouw, Indoor	L135 x W39 x H135
	320859 Tube Micro R Messing 680lm 2700K Ra 98 Fase afsnijding 15W LED 45 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	Fase afsnijding	Inbouw, Indoor	L135 x W39 x H135
	320750 Tube Micro R Wit 680lm 2700K Ra 98 DALI-2 15W LED 45 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	DALI-2	Inbouw, Indoor	L135 x W39 x H135
	320707 Tube Micro R Wit 680lm 2700K Ra 98 Fase afsnijding 15W LED 45 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	Fase afsnijding	Inbouw, Indoor	L135 x W39 x H135
	320754 Tube Micro R Zwart 700lm 3000K Ra 98 DALI-2 15W LED 47 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	DALI-2	Inbouw, Indoor	L135 x W39 x H135
	320711 Tube Micro R Zwart 700lm 3000K Ra 98 Fase afsnijding 15W LED 47 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector	Klasse II IP20	Fase afsnijding	Inbouw, Indoor	L135 x W39 x H135

Artikel	Bescherming	Regelapparaatuu	Montage/Aansluiting	Afmetingen	
	320751	Klasse II	DALI-2	Inbouw, Indoor	L135 x W39 x H135
	Tube Micro R Wit 700lm 3000K Ra	IP20			
	98 DALI-2				
	15W LED				
	47 lm/W SDCM:2				
	L90/B10>100,000				
Beam: 36°, Direct, Reflector					
	320708	Klasse II	Fase afsnijding	Inbouw, Indoor	L135 x W39 x H135
	Tube Micro R Wit 700lm 3000K Ra	IP20			
	98 Fase afsnijding				
	15W LED				
	47 lm/W SDCM:2				
	L90/B10>100,000				
Beam: 36°, Direct, Reflector					
Accessoires					
	9143				Ø133 x L133 x W133 x H4
	Rehab Ring Zwart 133mm voor Junistar, Uniled, Soft & Jupiter				
	9236				Ø180 x H45
	Rehab Ring Zwart 180mm voor Junistar, Uniled, Soft & Jupiter				
	320681				Ø37 x H11
	Tube Micro Zwart Ø39 Frontring				
	320682				Ø37 x H11
	Tube Micro Goud Ø39 Frontring				
	320756				Ø39 x H21
	Tube Micro Opaal 10mm Decoration ring				
	9223				Ø133 x L133 x W133 x H4
	Rehab Ring Wit 133mm voor Junistar, Uniled, Soft & Jupiter				
	9224				Ø180 x H45
	Rehab Ring Wit 180mm voor Junistar, Uniled, Soft & Jupiter				
	9227				Ø250 x H45
	Rehab Ring Wit 250mm voor Junistar, Uniled, Soft & Jupiter				



Artikel	Bescherming	Regelapparaatuu	Montage/Aansluiting	Afmetingen
 320680 Tube Micro Wit Ø39 Frontring		r		Ø37 x H11