

Lichtbronnen GU10



GU10 LED dimmable light source with five-year system warranty if used together with a SG luminaire.

Lichtbronnen GU10



Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 830984 GU10 Geborsteld Staal DimToWarm 345lm 2000-2800K Ra>90 6W LED 58 lm/W SDCM:3 L70/B50>50,000 Beam: 36°, Direct,		r	Fase afsnijding	L55 x W50 x H50
 830983 GU10 Wit DimToWarm 345lm 2000-2800K Ra>90 6W LED 58 lm/W SDCM:3 L70/B50>50,000 Beam: 36°, Direct,			Fase afsnijding	L55 x W50 x H50
 830962 GU10 Geborsteld Staal 360lm 2700K Ra>90 6W LED 60 lm/W SDCM:2 L70/B50>50,000 Beam: 32°, Direct,			Fase afsnijding	L55 x W50 x H50
 830980 GU10 Zilver 450lm 2700K Ra>80 6.2W LED 73 lm/W SDCM:4 L70/B50>25,000 Beam: 36°, Direct,			Fase afsnijding	L65 x W50 x H50
 830960 GU10 Wit 360lm 2700K Ra>90 6W LED 60 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Direct,			Fase afsnijding	L55 x W50 x H50
 830981 GU10 Zilver 455lm 3000K Ra>80 6.2W LED 73 lm/W SDCM:4 L70/B50>25,000 Beam: 36°, Direct,			Fase afsnijding	L65 x W50 x H50

Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 830961 GU10 Wit 375lm 3000K Ra>90 6W LED 63 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Direct,		r	Fase afsnijding	L55 x W50 x H50
 830982 GU10 Zilver 480lm 4000K Ra>80 6.2W LED 77 lm/W SDCM:4 L70/B50>25,000 Beam: 36°, Direct,			Fase afsnijding	L65 x W50 x H50