

Langfoss Mini



Langfoss is a powerful floodlight luminaire suitable for lighting large spaces, transport and storage areas, playgrounds, courts and car parks. Can also be used as facade lighting. Nordic design for Nordic conditions. The sloping top allows snow to slide off, and the bracket can withstand heavy loads. Asymmetrical optics send the light where it is needed, and the mounting bracket can be angled as required. Super simple installation with two-piece mounting bracket with hooks. Die-cast powder-coated aluminium with tempered glass front. Accessories for flexible installation: post for mounting top, post for mounting sides, corner bracket and extension cable.

Langfoss Mini



Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 641931 Langfoss Mini Grafiet 8640lm 3000K Ra>70 DALI-2 68W LED 127 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Asymmetrisch, Lens	Klasse I IP66 IK07	DALI-2	Indoor / Outdoor Kabel 5x1mm ² 2m, H07RN-F	L362 x W265 x H85
 641938 Langfoss Mini Grafiet 4850lm 3000K Ra>70 Niet dimbaar 35W LED 139 lm/W SDCM:3 L80/B50>100,000, L94>50,000 Asymmetrisch, Lens	Klasse I IP66 IK07	Niet dimbaar	Indoor / Outdoor Kabel 3x1mm ² 2m, H07RN-F	L362 x W265 x H85
 641939 Langfoss Mini Grafiet 8640lm 3000K Ra>70 Niet dimbaar 68W LED 127 lm/W SDCM:3 L80/B50>100,000, L94>50,000 Asymmetrisch, Lens	Klasse I IP66 IK07	Niet dimbaar	Indoor / Outdoor Kabel 3x1mm ² 2m, H07RN-F	L362 x W265 x H85
 641933 Langfoss Mini Grafiet 9330lm 4000K Ra>70 DALI-2 68W LED 137 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Asymmetrisch, Lens	Klasse I IP66 IK07	DALI-2	Indoor / Outdoor Kabel 5x1mm ² 2m, H07RN-F	L362 x W265 x H85
 641940 Langfoss Mini Grafiet 5240lm 4000K Ra>70 Niet dimbaar 35W LED 150 lm/W SDCM:3 L80/B50>100,000, L94>50,000 Asymmetrisch, Lens	Klasse I IP66 IK07	Niet dimbaar	Indoor / Outdoor Kabel 3x1mm ² 2m, H07RN-F	L362 x W265 x H85
 641941 Langfoss Mini Grafiet 9330lm 4000K Ra>70 Niet dimbaar 68W LED 137 lm/W SDCM:3 L80/B50>100,000, L94>50,000 Asymmetrisch, Lens	Klasse I IP66 IK07	Niet dimbaar	Indoor / Outdoor Kabel 3x1mm ² 2m, H07RN-F	L362 x W265 x H85

Artikel	Bescherming	Regelapparaatuu r	Montage/Aansluiting	Afmetingen
	641916 Langfoss Mini Grafiet Hoekbeugel			L139 x W249 x H180
	641917 Langfoss Mini Ø60/76 Grafiet Paalbeugel bovenkant			L142 x W249 x H112
	641918 Langfoss Mini Ø60/76 Grafiet Paalbeugel			L67 x W249 x H89
	641919 Langfoss Mini Ø89/108 Grafiet Paalbeugel			L67 x W249 x H89
	641949 Langfoss/Mini/Maxi Grafiet Bevestigingsplaat voor sandwichpanelen			L430 x W250 x H7
	820259 Startstroombegrenzer DIN 16A			L90 x W18 x H58