



Attractive, round LED wall/ceiling luminaire for indoor mounting. Made of painted metal. Diffuser made of UV-stabilised opal polycarbonate. Efficient LED board with long service life. Hatch for easy access to connection, and option of both visible and concealed cabling as well as loopable quick clips. Vandal-resistant rating IK10.

Orion



Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 212105 Orion Zwart 760lm 2700K Ra>80 Fase afsnijding 8W LED 95 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opaal	Klasse II IP20 IK10	r Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø300 x H87
 212100 Orion Wit 770lm 2700K Ra>80 Fase afsnijding 8W LED 96 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opaal	Klasse II IP20 IK10	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø300 x H87
 212139 Orion Wit 1480lm 2700K Ra>80 Fase afsnijding 15W LED 99 lm/W SDCM:3 L70/B10>50,000 Beam: 110°, Direct, Opaal	Klasse II IP20 IK10	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø300 x H87
 212134 Orion Wit 1510lm 3000K Ra>80 Sensor Dim 15W LED 101 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opaal	Klasse II IP20 IK10	Sensor Dim	Opbouw, Indoor Schroefloos klemmenblok	Ø300 x H87
 212110 Orion Wit 800lm 3000K Ra>80 Fase afsnijding 8W LED 100 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opaal	Klasse II IP20 IK10	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø300 x H87
 212115 Orion Wit 1510lm 3000K Ra>80 Fase afsnijding 15W LED 101 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opaal	Klasse II IP20 IK10	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø300 x H87

Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 212135 Orion Wit 1540lm 4000K Ra>80 Sensor Dim 15W LED 103 lm/W SDCM:3 L80/B10>50,000 Beam: 110°, Direct, Opaal	Klasse II	Sensor Dim	Opbouw, Indoor Schroefloos klemmenblok	Ø300 x H87
	IP20 IK10			
 212125 Orion Wit 1540lm 4000K Ra>80 Fase afsnijding 15W LED 103 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opaal	Klasse II	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø300 x H87
	IP20 IK10			