



Mirror luminaire made of aluminium with diffuser made of Acrylic (PMMA). Can be installed with either with concealed or visible cable. Design: Hallvard Jakobsen

## Product- en omgevingsbeelden



| Artikel                                                                            |                                                                    | Bescherming                          | Regelapparaat   | Montage/Aansluiting                       | Afmetingen             |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------|--------------------------------------|-----------------|-------------------------------------------|------------------------|
|    | 111340                                                             | Klasse I                             | Fase afsnijding | Opbouw, Indoor<br>Schroefloos klemmenblok | L510 x W70 x H80 x D80 |
|                                                                                    | <b>Prelude Wit 1050lm 2700K Ra&gt;90</b>                           | <b>IP44 (mounted horizontally) /</b> |                 |                                           |                        |
|                                                                                    | <b>Fase afsnijding</b>                                             | <b>IP20 (mounted vertically)</b>     |                 |                                           |                        |
|                                                                                    | <b>11W LED</b>                                                     | <b>IK05</b>                          |                 |                                           |                        |
|                                                                                    | 95 lm/W SDCM:3<br>L90/B10>50,000, L80/B10>100,000<br>Direct, Opaal |                                      |                 |                                           |                        |
|    | 111345                                                             | Klasse I                             | Fase afsnijding | Opbouw, Indoor<br>Schroefloos klemmenblok | L510 x W70 x H80 x D80 |
|                                                                                    | <b>Prelude Wit 1090lm 3000K Ra&gt;90</b>                           | <b>IP44 (mounted horizontally) /</b> |                 |                                           |                        |
|                                                                                    | <b>Fase afsnijding</b>                                             | <b>IP20 (mounted vertically)</b>     |                 |                                           |                        |
|                                                                                    | <b>11W LED</b>                                                     | <b>IK05</b>                          |                 |                                           |                        |
|                                                                                    | 99 lm/W SDCM:3<br>L90/B10>50,000, L80/B10>100,000<br>Direct, Opaal |                                      |                 |                                           |                        |
|    | 111346                                                             | Klasse I                             | Fase afsnijding | Opbouw, Indoor<br>Schroefloos klemmenblok | L560 x W70 x H80 x D80 |
|                                                                                    | <b>Prelude Wit met stopcontact</b>                                 | <b>IP44 (mounted horizontally) /</b> |                 |                                           |                        |
|                                                                                    | <b>1090lm 3000K Ra&gt;90 Fase</b>                                  | <b>IP20 (mounted vertically)</b>     |                 |                                           |                        |
|                                                                                    | <b>afsnijding</b>                                                  | <b>IK05</b>                          |                 |                                           |                        |
|                                                                                    | <b>11W LED</b>                                                     |                                      |                 |                                           |                        |
|  | 111347                                                             | Klasse I                             | Fase afsnijding | Opbouw, Indoor<br>Schroefloos klemmenblok | W560 x H70 x D80       |
|                                                                                    | <b>Prelude Wit met stopcontact</b>                                 | <b>IP44 (mounted horizontally) /</b> |                 |                                           |                        |
|                                                                                    | <b>1090lm 3000K Ra&gt;90 Fase</b>                                  | <b>IP20 (mounted vertically)</b>     |                 |                                           |                        |
|                                                                                    | <b>afsnijding</b>                                                  | <b>IK05</b>                          |                 |                                           |                        |
|                                                                                    | <b>11W LED</b>                                                     |                                      |                 |                                           |                        |
|                                                                                    | 99 lm/W SDCM:3<br>L90/B10>50,000, L80/B10>100,000<br>Direct, Opaal |                                      |                 |                                           |                        |