

Rax Soft 150



Rax Soft 150 is a high-performance downlight for lighting in public buildings, offices, corridors etc with an excellent light control by a combination of optimized lens and reflector optics. Available with satin matt reflector for high efficiency. Rax Soft 150 is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm.

Rax Soft 150



Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	Klasse II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Inbouw, Indoor Kabel 5x0,75mm ² 5-polige Linect / schroefloos klemmenblok	Ø166 x H83
	Klasse II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Inbouw, Indoor Kabel 5x0,75mm ² 5-polige Linect / schroefloos klemmenblok	Ø166 x H83
	Klasse II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Inbouw, Indoor Kabel 5x0,75mm ² 5-polige Linect / schroefloos klemmenblok	Ø166 x H83
	Klasse II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Inbouw, Indoor Kabel 5x0,75mm ² 5-polige Linect / schroefloos klemmenblok	Ø166 x H83
	Klasse II SELV IP54/IP20 IK08	Fase afsnijding	Inbouw, Indoor 3-polige Linect / schroefloos klemmenblok	Ø166 x H83

Artikel	Bescherming	Regelapparaatuu r	Montage/Aansluiting	Afmetingen
 212504 Rax Soft 150 Satin 2200 3000K Ra>80 Fase afsnijding 18W LED 119 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector	Klasse II SELV IP54/IP20 IK08	Fase afsnijding	Inbouw, Indoor 3-polige Linect / schroefloos klemmenblok	Ø166 x H83
 212506 Rax Soft 150 Satin 2200 3000K Ra>90 Fase afsnijding 22W LED 98 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector	Klasse II SELV IP54/IP20 IK08	Fase afsnijding	Inbouw, Indoor 3-polige Linect / schroefloos klemmenblok	Ø166 x H83
 212510 Rax Soft 150 Satin 3000 3000K Ra>80 Fase afsnijding 26W LED 114 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector	Klasse II SELV IP54/IP20 IK08	Fase afsnijding	Inbouw, Indoor 3-polige Linect / schroefloos klemmenblok	Ø166 x H83
 212503 Rax Soft 150 Satin 1600 4000K Ra>80 DALI-2 / Push Dim 13W LED 127 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector	Klasse II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Inbouw, Indoor Kabel 5x0,75mm² 5-polige Linect / schroefloos klemmenblok	Ø166 x H83
 212509 Rax Soft 150 Satin 2200 4000K Ra>80 DALI-2 / Push Dim 18W LED 123 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector	Klasse II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Inbouw, Indoor Kabel 5x0,75mm² 5-polige Linect / schroefloos klemmenblok	Ø166 x H83

Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	Klasse II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Inbouw, Indoor Kabel 5x0,75mm ² 5-polige Linect / schroefloos klemmenblok	Ø166 x H83
212513 Rax Soft 150 Satin 3000 4000K Ra>80 DALI-2 / Push Dim 26W LED 118 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector				
	Klasse II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Inbouw, Indoor Kabel 5x0,75mm ² 5-polige Linect / schroefloos klemmenblok	Ø166 x H83
212571 Rax Soft 150 Satin 2200 4000K Ra>90 DALI-2 / Push Dim 22W LED 105 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector				
	Klasse II SELV IP54/IP20 IK08	Fase afsnijding	Inbouw, Indoor 3-polige Linect / schroefloos klemmenblok	Ø166 x H83
212502 Rax Soft 150 Satin 1600 4000K Ra>80 Fase afsnijding 13W LED 127 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector				
	Klasse II SELV IP54/IP20 IK08	Fase afsnijding	Inbouw, Indoor 3-polige Linect / schroefloos klemmenblok	Ø166 x H83
212508 Rax Soft 150 Satin 2200 4000K Ra>80 Fase afsnijding 18W LED 123 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector				
	Klasse II SELV IP54/IP20 IK08	Fase afsnijding	Inbouw, Indoor 3-polige Linect / schroefloos klemmenblok	Ø166 x H83
212512 Rax Soft 150 Satin 3000 4000K Ra>80 Fase afsnijding 26W LED 118 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector				

Artikel		Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	212570	Klasse II SELV IP54/IP20 IK08	r		
	Rax Soft 150 Satin 2200 4000K Ra>90 Fase afsnijding 22W LED 105 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satijnmatte reflector		Fase afsnijding	Inbouw, Indoor 3-polige Linect / schroefloos klemmenblok	Ø166 x H83
Accessoires					
	212617				Ø220 x H16
	Rax 150 Zwart Rehabring Ø155-200mm				
	212621				Ø168 x H12
	Rax 150 Zwart Helder glas IP44				
	212623				Ø168 x H12
	Rax 150 Zwart Mat glas IP44				
	212620				Ø168 x H12
	Rax 150 Wit Helder glas IP44				
	212622				Ø168 x H12
	Rax 150 Wit Mat glas IP44				
	820489				L220 x W75 x H34
	Sensor Dim Box Wit 200VA				
	8249044683				Ø220 x H16
	Rax 150 Wit Rehabring Ø155-200mm				
	8246094364				L270 x W75 x H35
	Noodbox On-Off/Fase afsnijding / EM Self test, Nood 3h				
	8246094500				L270 x W75 x H35
	Noodbox Driver DALI / EM DALI/Self test, Nood 3h				
	8249042216				L585 x W260 x H15
	Rax 150 Montageplaat				