

Sense Opalprism TW



The Sense panel is well designed and only 10 mm high. A narrow frame ensures attractive look and high efficiency. Sense can be mounted to visible T-rail ceilings without accessories and to concealed T-rail ceilings, DAMPA clip-in ceilings, Troldekt acoustic panels and Gypsum, and surface-mounted using accessories. This makes Sense an all-round quality panel that can be used everywhere. Sense is available in Tunable White 2700-6500K LEDDim or DALI Type 8 depending on whichever driver kit is selected (accessory).

Sense Opalprism TW




Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	212315			
	Sense TW 600x600 Wit Opalprisma		Inbouw, Indoor	L597 x W597 x H10
	4000lm 2700-6500K Ra>80		Quick connector	
	LED			
	SDCM:3 L80/B20>100,000 Direct, Opalprisma			
Driver				
	820239	Klasse II	TW DALI Type 8	L215 x W70 x H32
	Sense TW Driver Wit 4000lm 38W		Indoor	
	TW DALI Type 8		5-polige Linect / schroefloos	
	38W		klemmenblok	
	820093	Klasse II	TW LEDDim	Indoor
	Sense TW Wit 4000lm 40W TW			3-polige Linect / schroefloos
	LEDDim			klemmenblok
	40W			
Accessoires				
	212256			L604 x W604 x H48
	Sense 600x600 Wit Opbouw kader			
	212688			L597 x W597 x H79
	Sense Decor Sky Wit 600x600			
	212780			L595 x W595 x H17
	Sense Decor Soft Wit 600x600			
	8249045006			L640 x W640 x H40
	Sense 600x600 Wit Gipsplaat/Troldtekt Inbouw kader			
	212170			L2000
	Sense 2m Pendelkit			
	8246094364			L270 x W75 x H35
	Noodbox On-Off/Fase afsnijding / EM Self test, Nood 3h			



Artikel	Bescherming	Regelapparaatuu r	Montage/Aansluiting	Afmetingen
 8246094500 Noodbox Driver DALI / EM DALI/Self test, Nood 3h				L270 x W75 x H35