

Sense Basic 300x600




The Sense Basic 300x600 LED panel is ideal both for new installations and remodelling projects. It can directly replace 2x14W T5 and 2x18W T8 luminaires. It has a lightweight steel housing and is based on backlight, yet it is only 35 mm height. High quality non-yellowing PMMA micro prismatic front optics. Easy tool-free installation, twist connector between driver and panel and junction box with automatic strain relief for cables or plastic tubing.

Sense Basic 300x600



Product- en omgevingsbeelden



Artikel		Bescherming	Regelapparaatu r	Montage/Aansluiting	Afmetingen
	212146 Sense Basic 300x600 Wit 2180lm 3000K Ra>80 Niet dimbaar 20W LED 109 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprisma	Klasse II IP20 IK06	Niet dimbaar	Indoor 3-polige Linect / schroefloos klemmenblok	L595 x W295 x H36 x D36
	212147 Sense Basic 300x600 Wit 2220lm 4000K Ra>80 Niet dimbaar 20W LED 111 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprisma	Klasse II IP20 IK06	Niet dimbaar	Indoor 3-polige Linect / schroefloos klemmenblok	L595 x W295 x H36 x D36
Accessoires					
	8246094364 Noodbox On-Off/Fase afsnijding / EM Self test, Nood 3h				L270 x W75 x H35
	8246094500 Noodbox Driver DALI / EM DALI/Self test, Nood 3h				L270 x W75 x H35