

Bell



Ceiling lamp with deep-mounted light source that provides a comfortable light without glare. Supplied with a ceiling rose. Can also be fitted in adapters for Zip 230V rails and ShopLine 3-phase rails. Bell comes in three sizes and three different color combinations: Black/White, White/White and Black/Gold.

Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 312362 Bell Zwart/Goud Mini 240lm 2700K Ra>90 Fase afsnijding 5W LED 48 lm/W SDCM:3 L70/B50>50,000 Beam: 137°, Direct/Indirect, Opaal	Klasse II IP20	Fase afsnijding	Opbouw, Indoor Kabel 3m Schroefloos klemmenblok	Ø160 x H205
 312365 Bell Zwart/Goud Midi 560lm 2700K Ra>90 Fase afsnijding 10W LED 56 lm/W SDCM:3 L70/B50>50,000 Beam: 127°, Direct/Indirect, Opaal	Klasse II IP20	Fase afsnijding	Opbouw, Indoor Kabel 3m Schroefloos klemmenblok	Ø230 x H261
 312368 Bell Zwart/Goud Maxi 820lm 2700K Ra>90 Fase afsnijding 15W LED 55 lm/W SDCM:3 L70/B50>50,000 Beam: 130°, Direct/Indirect, Opaal	Klasse II IP20	Fase afsnijding	Opbouw, Indoor Kabel 3m Schroefloos klemmenblok	Ø300 x H317
 312361 Bell Zwart/Wit Mini 250lm 2700K Ra>90 Fase afsnijding 5W LED 50 lm/W SDCM:3 L70/B50>50,000 Beam: 100°, Direct/Indirect, Opaal	Klasse II IP20	Fase afsnijding	Opbouw, Indoor Kabel 3m Schroefloos klemmenblok	Ø160 x H205
 312364 Bell Zwart/Wit Midi 590lm 2700K Ra>90 Fase afsnijding 10W LED 59 lm/W SDCM:3 L70/B50>50,000 Beam: 106°, Direct/Indirect, Opaal	Klasse II IP20	Fase afsnijding	Opbouw, Indoor Kabel 3m Schroefloos klemmenblok	Ø230 x H261
 312367 Bell Zwart/Wit Maxi 840lm 2700K Ra>90 Fase afsnijding 15W LED 56 lm/W SDCM:3 L70/B50>50,000 Beam: 104°, Direct/Indirect, Opaal	Klasse II IP20	Fase afsnijding	Opbouw, Indoor Kabel 3m Schroefloos klemmenblok	Ø300 x H317

Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	312369	Klasse II	Fase afsnijding	Ø160 x H205
	Bell Wit/Goud Mini 240lm 2700K	IP20	Kabel 3m	
	Ra>90 Fase afsnijding		Schroefloos klemmenblok	
	5W LED			
	48 lm/W SDCM:3 L70/B50>50,000 Direct/Indirect, Opaal			
	312370	Klasse II	Fase afsnijding	Ø230 x H261
	Bell Wit/Goud Midi 560lm 2700K	IP20	Kabel 3m	
	Ra>90 Fase afsnijding		Schroefloos klemmenblok	
	10W LED			
	56 lm/W SDCM:3 L70/B50>50,000 Direct/Indirect, Opaal			
	312371	Klasse II	Fase afsnijding	Ø300 x H317
	Bell Wit/Goud Maxi 820lm 2700K	IP20	Kabel 3m	
	Ra>90 Fase afsnijding		Schroefloos klemmenblok	
	15W LED			
	55 lm/W SDCM:3 L70/B50>50,000 Direct/Indirect, Opaal			
Accessoires				
	830917			Ø95 x L135
	E27 LED Wit DimToWarm 1200lm 2000-2800K Ra>80			
	830922			Ø45 x L79
	E27 LED Wit DimToWarm 350lm 2000-2800K Ra>80			
	830913			Ø60 x L110
	E27 LED DimToWarm 806lm 2000-2800K Ra>80			
	830916			Ø95 x L136
	E27 LED Wit 1200lm 2700K Ra>90			
	830911			Ø60 x L110
	E27 806lm 2700K Ra>90			
	830918			Ø95 x L136
	E27 LED Wit 1200lm 3000K Ra>90			

Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	3107 Zip 230V Zwart Adapter - Pendel			L84 x W23 x H90
	3109 Shipline Zwart Pendel Adapter			L93 x W32 x H62
	3163 Zwart Plafonddoos voor Pendel			Ø114 x L135 x W114
	314331 Zwart Ronde Plafonddoos voor Pendel			Ø102 x L102 x W102 x H25
	314334 Zwart Inbouw Plafonddoos voor Pendel			Ø94 x H51
	3046 Zip 230V Wit Adapter - Pendel			L84 x W23 x H90
	3108 Shipline Wit Pendel Adapter			L93 x W32 x H62
	3164 Wit Plafonddoos voor Pendel			Ø114 x L135 x W114
	314332 Wit Ronde Plafonddoos voor Pendel			Ø102 x L102 x W102 x H25
	314333 Wit Inbouw Plafonddoos voor Pendel			Ø94 x H51