



Farm 66 is a very hardy luminaire, especially suitable for pig farms and the like. The LED compartment has an extra high protection rating to withstand ammonia gasses in such environments. The luminaire housing is made of hard UV-stabilised and anti-chemical coated polycarbonate. The coating is resistant to ammonia, washing detergents* etc, and makes it suitable also for car wash halls and similar. It is easy to install by just snapping into mounting clips and using the unique one-hand closing mechanism at both ends. The looping options with double cable gland in each end and through wiring gives full flexibility for larger installations. * Farm 66 is resistant to aqueous salt solutions up to about 60°C and diluted acids. It has limited resistance to alcohols, aliphatic hydrocarbons, and diluted alkalis, and is not resistant to concentrated mineral acids and alkalis, ammonia, amines, aromatic and/or halogenated hydrocarbons, esters, ethers, ketones, or solvents such as methyl ethylketone, tetrahydrofuran, toluene, and dimethyl-formamide.

Product- en omgevingsbeelden



Artikel		Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	120012	Klasse I	DALI-2 / Push Dim	Opbouw, Indoor 7-polig schroefloos klemmenblok met 5x2,5mm² (+DALI) doorvoerbedrading	L1460 x W112 x H67
	Farm 66 1500 Grijs 5860lm 4000K	IP66			
	Ra>80 DALI-2 / Push Dim	IK08			
	43W LED				
	136 lm/W SDCM:3 L90/B50>50,000 Direct, Opaal				
	120014	Klasse I	DALI-2 / Push Dim	Opbouw, Indoor 7-polig schroefloos klemmenblok met 5x2,5mm² (+DALI) doorvoerbedrading	L1460 x W112 x H67
	Farm 66 Pro 1500 Grijs 9820lm	IP66			
	4000K Ra>80 DALI-2 / Push Dim	IK08			
	65W LED				
	151 lm/W SDCM:3 L80/B10>100,000 Direct, Opaal				
	120009	Klasse I	Niet dimbaar	Opbouw, Indoor 5-polig schroefloos klemmenblok met 5x2,5mm² doorvoerbedrading	L1174 x W112 x H67
	Farm 66 1200 Grijs 4030lm 4000K	IP66			
	Ra>80 Niet dimbaar	IK08			
	34W LED				
	119 lm/W SDCM:3 L90/B50>50,000 Direct, Opaal				
	120010	Klasse I	Niet dimbaar	Opbouw, Indoor 5-polig schroefloos klemmenblok met 5x2,5mm² doorvoerbedrading	L1460 x W112 x H67
	Farm 66 1500 Grijs 5720lm 4000K	IP66			
	Ra>80 Niet dimbaar	IK08			
	47W LED				
	122 lm/W SDCM:3 L90/B50>50,000 Direct, Opaal				
Accessoires					
	120006				L42 x W42 x H15
	45° Plafondbeugels				
	820259				L90 x W18 x H58
	Startstroombegrenzer DIN 16A				
	8249044900				L19 x W25 x H150
	Pendelkit 2x5m				