

Inspire R TW




Inspire R TW is a rectangular recessed downlight for indoor use. With cubist black reflectors it has very low glare and harmonious non-flickering light with a well-defined light pattern. Inspire R TW is suitable for use in high-end residential and commercial environments. Tunable White from 2000-4000K or 2700-6500K. Controlled by TW LEDDim or DALI Type 8 (DALI Type 8 only version 300).

Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 212446 Inspire R Zwart 300 970lm (@4000K) 2000-4000K Ra>90 TW DALI Type 8 17W LED 57 lm/W SDCM:2 L90/B10>100,000 Beam: 55°, Direct, Lens	Klasse II SELV IP20	TW DALI Type 8	Inbouw, Indoor Schroefloos klemmenblok	L303 x W62 x H40
 212440 Inspire R Zwart 150 500lm (@4000K) 2000-4000K Ra>90 TW LEDDim 10W LED 50 lm/W SDCM:2 L90/B10>100,000 Beam: 55°, Direct, Lens	Klasse II SELV IP20	TW LEDDim	Inbouw, Indoor Schroefloos klemmenblok	L163 x W62 x H40
 212442 Inspire R Zwart 300 970lm (@4000K) 2000-4000K Ra>90 TW LEDDim 17W LED 57 lm/W SDCM:2 L90/B10>100,000 Beam: 55°, Direct, Lens	Klasse II SELV IP20	TW LEDDim	Inbouw, Indoor Schroefloos klemmenblok	L303 x W62 x H40
 212445 Inspire R Wit 300 970lm (@4000K) 2000-4000K Ra>90 TW DALI Type 8 17W LED 57 lm/W SDCM:2 L90/B10>100,000 Beam: 55°, Direct, Lens	Klasse II SELV IP20	TW DALI Type 8	Inbouw, Indoor Schroefloos klemmenblok	L303 x W62 x H40
 212439 Inspire R Wit 150 500lm (@4000K) 2000-4000K Ra>90 TW LEDDim 10W LED 50 lm/W SDCM:2 L90/B10>100,000 Beam: 55°, Direct, Lens	Klasse II SELV IP20	TW LEDDim	Inbouw, Indoor Schroefloos klemmenblok	L163 x W62 x H40
 212441 Inspire R Wit 300 970lm (@4000K) 2000-4000K Ra>90 TW LEDDim 17W LED 57 lm/W SDCM:2 L90/B10>100,000	Klasse II SELV IP20	TW LEDDim	Inbouw, Indoor Schroefloos klemmenblok	L303 x W62 x H40

Artikel	Beam: 55°, Direct, Lens	Bescherming	Regelapparaatuu r	Montage/Aansluiting	Afmetingen
 212453 Inspire R Zwart 300 1080lm (@6500K) 2700-6500K Ra>90 TW DALI Type 8 17W LED 64 lm/W SDCM:2 L90/B10>100,000 Beam: 55°, Direct, Lens		Klasse II SELV IP20	TW DALI Type 8	Inbouw, Indoor Schroefloos klemmenblok	L303 x W62 x H40
 212449 Inspire R Zwart 150 560lm (@6500K) 2700-6500K Ra>90 TW LEDDim 10W LED 56 lm/W SDCM:2 L90/B10>100,000 Beam: 55°, Direct, Lens		Klasse II SELV IP20	TW LEDDim	Inbouw, Indoor Schroefloos klemmenblok	L163 x W62 x H40
 212452 Inspire R Zwart 300 1080lm (@6500K) 2700-6500K Ra>90 TW LEDDim 17W LED 64 lm/W SDCM:2 L90/B10>100,000 Beam: 55°, Direct, Lens		Klasse II SELV IP20	TW LEDDim	Inbouw, Indoor Schroefloos klemmenblok	L303 x W62 x H40
 212451 Inspire R Wit 300 1080lm (@6500K) 2700-6500K Ra>90 TW DALI Type 8 17W LED 64 lm/W SDCM:2 L90/B10>100,000 Beam: 55°, Direct, Lens		Klasse II SELV IP20	TW DALI Type 8	Inbouw, Indoor Schroefloos klemmenblok	L303 x W62 x H40
 212448 Inspire R Wit 150 560lm (@6500K) 2700-6500K Ra>90 TW LEDDim 10W LED 56 lm/W SDCM:2 L90/B10>100,000 Beam: 55°, Direct, Lens		Klasse II SELV IP20	TW LEDDim	Inbouw, Indoor Schroefloos klemmenblok	L163 x W62 x H40
 212450 Inspire R Wit 300 1080lm (@6500K) 2700-6500K Ra>90 TW LEDDim 17W LED 64 lm/W SDCM:2 L90/B10>100,000		Klasse II SELV IP20	TW LEDDim	Inbouw, Indoor Schroefloos klemmenblok	L303 x W62 x H40
Accessoires					

Artikel	Beam: 55°, Direct, Lens	Bescherming	Regelapparaat r	Montage/Aansluiting	Afmetingen
	212482				L140 x W38 x H16
	Inspire Goud 150 Reflector				
	212483				L280 x W38 x H16
	Inspire Goud 300 Reflector				
	212480				L140 x W38 x H16
	Inspire Wit 150 Reflector				
	212481				L280 x W38 x H16
	Inspire Wit 300 Reflector				
	820090				L250 x W13 x H13
	Noodbox Adapter kit voor downlight				
	8246094364				L270 x W75 x H35
	Noodbox On-Off/Fase afsnijding / EM Self test, Nood 3h				
	8246094500				L270 x W75 x H35
	Noodbox Driver DALI / EM DALI/Self test, Nood 3h				