

Sense IP65 Eco



Sense IP65 Eco is a waterproof luminaire with opal prismatic front, delivered complete with driver. Ideal for industrial kitchens, hospitals, laboratories, and production facilities. Very low glare, UGR

Sense IP65 Eco




Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	212468	Klasse II	DALI-2	L597 x W597 x H53
	Sense IP65 Eco Wit 4060lm 3000K	IP65	Inbouw, Indoor	
	Ra>80 DALI-2		5-polige Linect / schroefloos	
	34W LED		klemmenblok	
	119 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Direct, Opalprisma			
	212390	Klasse II	Fase afsnijding	L597 x W597 x H53
	Sense IP65 Eco Wit 4060lm 3000K	IP65	Inbouw, Indoor	
	Ra>80 Fase afsnijding			
	34W LED			
	119 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Direct, Opalprisma			
	212414	Klasse II	DALI-2	L597 x W597 x H53
	Sense IP65 Eco Wit 4350lm 4000K	IP65	Inbouw, Indoor	
	Ra>80 DALI-2		5-polige Linect / schroefloos	
	34W LED		klemmenblok	
	128 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Direct, Opalprisma			
	212391	Klasse II	Fase afsnijding	L597 x W597 x H53
	Sense IP65 Eco Wit 4350lm 4000K	IP65	Inbouw, Indoor	
	Ra>80 Fase afsnijding			
	34W LED			
	128 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 89°, Direct, Opalprisma			
Accessoires				
	820489			L220 x W75 x H34
	Sensor Dim Box Wit 200VA			
	8249045006			L640 x W640 x H40
	Sense 600x600 Wit Gipsplaat/Troldtekt Inbouwkader			
	8246094364			L270 x W75 x H35
	Noodbox On-Off/Fase afsnijding / EM Self test, Nood 3h			



Artikel	Bescherming	Regelapparaatuu r	Montage/Aansluiting	Afmetingen
 8246094500 Noodbox Driver DALI / EM DALI/Self test, Nood 3h				L270 x W75 x H35