



EcoLine is a slim and stylish ceiling luminaire suitable for use in offices, schools and public buildings. Designed for quick and easy installation. Three-layer optical system with low glare: UGR

Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 212802 EcoLine 1600 Wit 4880lm 3000K Ra>80 DALI-2 36W LED 136 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprisma	Klasse I IP20	DALI-2	Ophanging of opbouw, Indoor 3+2-polig schroefloos klemmenblok	L1600 x W166 x H47
 212093 EcoLine 1200 Wit 3910lm 3000K Ra>80 DALI-2 / Push Dim 30W LED 130 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprisma	Klasse I IP20	DALI-2 / Push Dim	Ophanging of opbouw, Indoor 3+2-polig schroefloos klemmenblok	L1235 x W166 x H47
 212091 EcoLine 1200 Wit 3910lm 3000K Ra>80 Niet dimbaar 30W LED 130 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprisma	Klasse I IP20	Niet dimbaar	Ophanging of opbouw, Indoor 3-polig schroefloos klemmenblok	L1235 x W166 x H47
 212800 EcoLine 1600 Wit 4880lm 3000K Ra>80 Niet dimbaar 36W LED 136 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprisma	Klasse I IP20	Niet dimbaar	Ophanging of opbouw, Indoor 3-polig schroefloos klemmenblok	L1600 x W166 x H47
 212803 EcoLine 1600 Wit 5180lm 4000K Ra>80 DALI-2 36W LED 144 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprisma	Klasse I IP20	DALI-2	Ophanging of opbouw, Indoor 3+2-polig schroefloos klemmenblok	L1600 x W166 x H47
 212094 EcoLine 1200 Wit 4150lm 4000K Ra>80 DALI-2 / Push Dim 30W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct, Opalprisma	Klasse I IP20	DALI-2 / Push Dim	Ophanging of opbouw, Indoor 3+2-polig schroefloos klemmenblok	L1235 x W166 x H47

Artikel		Bescherming	Regelapparaatuu	Montage/Aansluiting	Afmetingen
	212092	Klasse I	Niet dimbaar	Ophanging of opbouw, Indoor 3-polig schroefloos klemmenblok	L1235 x W166 x H47
	EcoLine 1200 Wit 4150lm 4000K	IP20			
	Ra>80 Niet dimbaar				
	30W LED				
	138 lm/W SDCM:3				
	L90/B10>100,000, L96>50,000				
	Direct, Opalprisma				
	212801	Klasse I	Niet dimbaar	Ophanging of opbouw, Indoor 3-polig schroefloos klemmenblok	L1600 x W166 x H47
	EcoLine 1600 Wit 5180lm 4000K	IP20			
	Ra>80 Niet dimbaar				
	36W LED				
	144 lm/W SDCM:3				
	L90/B10>100,000, L96>50,000				
	Direct, Opalprisma				
Accessoires					
	212255				L596 x W35 x H17
	T-profil Wit Ophangrail 600mm				
	212095				L2000
	EcoLine Pendelkit				