



Junistar Bio sets a new standard for easy installation of downlights. New, patented, springs minimize the installation time. Junistar Bio can be installed in all false ceilings >2 mm, directly in insulation or in a downlightbox. The springs also work in concrete holes, and can therefore replace fixtures with flange springs. Build-in height of 56 mm. Install and dismount in a few seconds - without hurting the fingers. It includes a junction box that provides strain relief for several types of cables, as well as fixation for plastic tubing. Junistar Bio has super efficiency with high quality of light and no flicker. Phase cut dimmable and tiltable steps in two directions, totally 2x25°. The luminaire is developed with focus on sustainability and is produced with bio-circular material; made of waste and residues of biological origin. It also has less material than a traditional downlight: ~40% weight reduction. Supplied as an 8-pack.

Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 905253 Junistar Bio Zwart 470lm 2700K Ra>90 Fase afsnijding 5W LED 94 lm/W SDCM:2 L80/B20>50,000 Beam: 45°, Direct, Lens	Klasse II IP44/IP20	Fase afsnijding	Inbouw, Indoor Schroefloos klemmenblok	Ø94 x H59
 905250 Junistar Bio Wit 500lm 2700K Ra>90 Fase afsnijding 5W LED 100 lm/W SDCM:2 L80/B20>50,000 Beam: 45°, Direct, Lens	Klasse II IP44/IP20	Fase afsnijding	Inbouw, Indoor Schroefloos klemmenblok	Ø94 x H59
 905254 Junistar Bio Zwart 490lm 3000K Ra>90 Fase afsnijding 5W LED 98 lm/W SDCM:2 L80/B20>50,000 Beam: 45°, Direct, Lens	Klasse II IP44/IP20	Fase afsnijding	Inbouw, Indoor Schroefloos klemmenblok	Ø94 x H59
 905251 Junistar Bio Wit 520lm 3000K Ra>90 Fase afsnijding 5W LED 104 lm/W SDCM:2 L80/B20>50,000 Beam: 45°, Direct, Lens	Klasse II IP44/IP20	Fase afsnijding	Inbouw, Indoor Schroefloos klemmenblok	Ø94 x H59
 905255 Junistar Bio Zwart 510lm 4000K Ra>90 Fase afsnijding 5W LED 102 lm/W SDCM:2 L80/B20>50,000 Beam: 45°, Direct, Lens	Klasse II IP44/IP20	Fase afsnijding	Inbouw, Indoor Schroefloos klemmenblok	Ø94 x H59
 905252 Junistar Bio Wit 540lm 4000K Ra>90 Fase afsnijding 5W LED 108 lm/W SDCM:2 L80/B20>50,000 Beam: 45°, Direct, Lens	Klasse II IP44/IP20	Fase afsnijding	Inbouw, Indoor Schroefloos klemmenblok	Ø94 x H59

Accessoires



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 820489 Sensor Dim Box Wit 200VA		r		L220 x W75 x H34