

# Herning Bollard & Pole



With its combination of modern elegance and classic design, Herning Bollard is ideal for illuminating driveways, gardens, or other outdoor areas. Its glare-free light creates a pleasant atmosphere while providing optimal illumination. The bollard is compatible with both the Herning Mini and Midi pole heads, allowing you to create a cohesive look in your outdoor space with bollards, poles, and wall lights in the same timeless design. The bollard and pole head are sold separately. Herning Bollard is made from durable, powder-coated aluminum, and the luminaire has a tempered glass front. Behind the glass, you'll find practical switches that let you choose between 3000K or 4000K color temperatures, as well as two different light levels—offering four combinations in a single fixture. It comes preset to 3000K and the highest light level but can easily be adjusted to suit your lighting needs. This phase-cut dimmable bollard can be mounted directly on the ground or cast in with an anchor bracket (sold separately), and a mounting plate compatible with the Ørsta foundation is available as an accessory.

# Herning Bollard & Pole



## Product- en omgevingsbeelden



| Artikel                                                                             | Bescherming                      | Regelapparaatu | Montage/Aansluiting                                                                | Afmetingen         |
|-------------------------------------------------------------------------------------|----------------------------------|----------------|------------------------------------------------------------------------------------|--------------------|
|    | 623978                           | Klasse II      | Fase afsnijding<br><br>Paal, wand, sokkel of aardstaaf, Outdoor<br>Kabel 2x1mm² 3m | L342 x W182 x H144 |
|                                                                                     | Herning Poolhoofd Ø60 Zwart Mini | IP65           |                                                                                    |                    |
|                                                                                     | 580/620/1220/1300lm 3000/4000K   | IK06           |                                                                                    |                    |
|                                                                                     | Ra>80 Fase afsnijding            |                |                                                                                    |                    |
|                                                                                     | LED                              |                |                                                                                    |                    |
|                                                                                     | 73/78/72/76lm/W SDCM:3           |                |                                                                                    |                    |
|                                                                                     | L80/B20>50,000                   |                |                                                                                    |                    |
| Direct, Glas                                                                        |                                  |                |                                                                                    |                    |
|     | 623979                           | Klasse II      | Fase afsnijding<br><br>Paal, wand, sokkel of aardstaaf, Outdoor<br>Kabel 2x1mm² 3m | L400 x W240 x H189 |
|                                                                                     | Herning Poolhoofd Ø60 Zwart Midi | IP65           |                                                                                    |                    |
|                                                                                     | 1060/1140/1770/1920lm            | IK06           |                                                                                    |                    |
|                                                                                     | 3000/4000K Ra>80 Fase afsnijding |                |                                                                                    |                    |
|                                                                                     | LED                              |                |                                                                                    |                    |
|                                                                                     | 82/88/71/77lm/W SDCM:3           |                |                                                                                    |                    |
|                                                                                     | L80/B20>50,000                   |                |                                                                                    |                    |
| Direct, Glas                                                                        |                                  |                |                                                                                    |                    |
|   | 623980                           | Klasse II      | Fase afsnijding<br><br>Paal, wand, sokkel of aardstaaf, Outdoor<br>Kabel 2x1mm² 3m | L342 x W182 x H144 |
|                                                                                     | Herning Poolhoofd Ø60 Grijs Mini | IP65           |                                                                                    |                    |
|                                                                                     | 580/620/1220/1300lm 3000/4000K   | IK06           |                                                                                    |                    |
|                                                                                     | Ra>80 Fase afsnijding            |                |                                                                                    |                    |
|                                                                                     | LED                              |                |                                                                                    |                    |
|                                                                                     | 73/36/72/76lm/W SDCM:3           |                |                                                                                    |                    |
|                                                                                     | L80/B20>50,000                   |                |                                                                                    |                    |
| Direct, Glas                                                                        |                                  |                |                                                                                    |                    |
|   | 623981                           | Klasse II      | Fase afsnijding<br><br>Paal, wand, sokkel of aardstaaf, Outdoor<br>Kabel 2x1mm² 3m | L400 x W240 x H189 |
|                                                                                     | Herning Poolhoofd Ø60 Grijs Midi | IP65           |                                                                                    |                    |
|                                                                                     | 1060/1140/1770/1920lm            | IK06           |                                                                                    |                    |
|                                                                                     | 3000/4000K Ra>80 Fase afsnijding |                |                                                                                    |                    |
|                                                                                     | LED                              |                |                                                                                    |                    |
|                                                                                     | 82/88/71/77lm/W SDCM:3           |                |                                                                                    |                    |
|                                                                                     | L80/B20>50,000                   |                |                                                                                    |                    |
| Direct, Glas                                                                        |                                  |                |                                                                                    |                    |
| Accessoires                                                                         |                                  |                |                                                                                    |                    |
|  | 623972                           |                |                                                                                    | Ø60 x H2500        |
|                                                                                     | Herning Palen 2,5M Ø60 Zwart     |                |                                                                                    |                    |
|  | 623975                           |                |                                                                                    | Ø60 x H855         |
|                                                                                     | Herning Sokkellamp 900 Ø60 Zwart |                |                                                                                    |                    |

| Artikel                                                                           | Bescherming                                       | Regelapparaat | Montage/Aansluiting | Afmetingen                |
|-----------------------------------------------------------------------------------|---------------------------------------------------|---------------|---------------------|---------------------------|
|  | 623973<br><b>Herning Palen 2,5M Ø60 Grijs</b>     |               |                     | Ø60 x H2500               |
|  | 623976<br><b>Herning Sokkellamp 900 Ø60 Grijs</b> |               |                     | Ø60 x H855                |
|  | 623984<br><b>Fixingplate for Ørsta Foundation</b> |               |                     | L200 x W200 x H8          |
|  | 8249042067<br><b>Grondanker</b>                   |               |                     | Ø155 x L248 x W108 x H450 |