

Inspire Prism



Inspire Prism has a slim, modern design with powder-coated white or black outer surface. Direct light with prismatic, glare-free optics made of PMMA, combined with indirect light with a wide beam angle, gives an efficient light perfectly suited for offices and above desks. 2,5m cable and wireset for ceiling/T-profile fixing is included. Different control options are available; phase cut, pull-dim or DALI. If you want to position several luminaires in a row, the luminaires can easily be connected together with the supplied coupling piece or the flexible corner (accessory).

Inspire Prism




Product- en omgevingsbeelden






Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	Klasse I IP20	DALI-2	Ophanging, Indoor 2 X 2 m kabelkit Kabel 5x0,75mm ² 2,5m	L1240 x W38 x H67
212493 Inspire 1200 Zwart prismatische 3510lm 3000K Ra>80 DALI-2 29W LED 121 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek				
	Klasse I IP20	DALI-2	Ophanging, Indoor 2 X 2 m kabelkit Kabel 5x0,75mm ² 2,5m	L1465 x W38 x H67
212863 Inspire 1500 Zwart prismatische 4330lm 3000K Ra>80 DALI-2 35W LED 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek				
	Klasse I IP20	Dim 1x trekschakelaars	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
212492 Inspire 1200 Zwart prismatische 3510lm 3000K Ra>80 Dim 1x trekschakelaars 29W LED 121 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek				
	Klasse I IP20	Dim 1x trekschakelaars	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67
212862 Inspire 1500 Zwart prismatische 4330lm 3000K Ra>80 Dim 1x trekschakelaars 35W LED 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek				
	Klasse I IP20	PIR Sensor	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
212853 Inspire 1200 Zwart prismatische 3510lm 3000K Ra>80 PIR Sensor 29W LED 121 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek				
	Klasse I IP20	PIR Sensor	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67
212871 Inspire 1500 Zwart prismatische 4060lm 3000K Ra>80 PIR Sensor 34W LED 119 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek				

Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 212852 Inspire 1200 Zwart prismatische afsnijding 3510lm 3000K Ra>80 Fase 29W LED 121 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	Fase afsnijding	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
 212870 Inspire 1500 Zwart prismatische afsnijding 4330lm 3000K Ra>80 Fase 35W LED 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	Fase afsnijding	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67
 212491 Inspire 1200 Wit prismatische DALI-2 4000lm 3000K Ra>80 DALI-2 29W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	DALI-2	Ophanging, Indoor 2 X 2 m kabelkit Kabel 5x0,75mm ² 2,5m	L1240 x W38 x H67
 212861 Inspire 1500 Wit prismatische DALI-2 4800lm 3000K Ra>80 DALI-2 35W LED 137 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	DALI-2	Ophanging, Indoor 2 X 2 m kabelkit Kabel 5x0,75mm ² 2,5m	L1465 x W38 x H67
 212490 Inspire 1200 Wit prismatische trekschakelaars 4000lm 3000K Ra>80 Dim 1x 29W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	Dim 1x trekschakelaars	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
 212860 Inspire 1500 Wit prismatische trekschakelaars 4800lm 3000K Ra>80 Dim 1x 35W LED 137 lm/W SDCM:3	Klasse I IP20	Dim 1x trekschakelaars	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67

Artikel	L90/B10>100,000, L96>50,000	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
Direct/Indirect, Prismaoptiek			r		
	212851 Inspire 1200 Wit prismatische 4000lm 3000K Ra>80 PIR Sensor 29W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	PIR Sensor	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
	212869 Inspire 1500 Wit prismatische 4510lm 3000K Ra>80 PIR Sensor 34W LED 133 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	PIR Sensor	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67
	212850 Inspire 1200 Wit prismatische 4000lm 3000K Ra>80 Fase afsnijding 29W LED 138 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	Fase afsnijding	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
	212868 Inspire 1500 Wit prismatische 4800lm 3000K Ra>80 Fase afsnijding 35W LED 137 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	Fase afsnijding	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67
	212497 Inspire 1200 Zwart prismatische 3620lm 4000K Ra>80 DALI-2 29W LED 125 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	DALI-2	Ophanging, Indoor 2 X 2 m kabelkit Kabel 5x0,75mm ² 2,5m	L1240 x W38 x H67
	212867 Inspire 1500 Zwart prismatische 4470lm 4000K Ra>80 DALI-2 35W LED 128 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	DALI-2	Ophanging, Indoor 2 X 2 m kabelkit Kabel 5x0,75mm ² 2,5m	L1465 x W38 x H67

Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
 212496 Inspire 1200 Zwart prismatische 3620lm 4000K Ra>80 Dim 1x trekschakelaars 29W LED 125 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	Dim 1x trekschakelaars	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
 212866 Inspire 1500 Zwart prismatische 4470lm 4000K Ra>80 Dim 1x trekschakelaars 35W LED 128 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	Dim 1x trekschakelaars	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67
 212857 Inspire 1200 Zwart prismatische 3620lm 4000K Ra>80 PIR Sensor 29W LED 125 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	PIR Sensor	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
 212875 Inspire 1500 Zwart prismatische 4200lm 4000K Ra>80 PIR Sensor 34W LED 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	PIR Sensor	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67
 212856 Inspire 1200 Zwart prismatische 3620lm 4000K Ra>80 Fase afsnijding 29W LED 125 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	Fase afsnijding	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
 212874 Inspire 1500 Zwart prismatische 4470lm 4000K Ra>80 Fase afsnijding 35W LED 128 lm/W SDCM:3	Klasse I IP20	Fase afsnijding	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67

Artikel	L90/B10>100,000, L96>50,000	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
Direct/Indirect, Prismaoptiek			r		
	212495 Inspire 1200 Wit prismatiche 4130lm 4000K Ra>80 DALI-2 29W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	DALI-2	Ophanging, Indoor 2 X 2 m kabelkit Kabel 5x0,75mm ² 2,5m	L1240 x W38 x H67
	212865 Inspire 1500 Wit prismatiche 4960lm 4000K Ra>80 DALI-2 35W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	DALI-2	Ophanging, Indoor 2 X 2 m kabelkit Kabel 5x0,75mm ² 2,5m	L1465 x W38 x H67
	212494 Inspire 1200 Wit prismatiche 4130lm 4000K Ra>80 Dim 1x trekschakelaars 29W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	Dim 1x trekschakelaars	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
	212864 Inspire 1500 Wit prismatiche 4960lm 4000K Ra>80 Dim 1x trekschakelaars 35W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	Dim 1x trekschakelaars	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67
	212855 Inspire 1200 Wit prismatiche 4130lm 4000K Ra>80 PIR Sensor 29W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	PIR Sensor	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
	212873 Inspire 1500 Wit prismatiche 4660lm 4000K Ra>80 PIR Sensor 34W LED 137 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek	Klasse I IP20	PIR Sensor	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67

Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	Klasse I IP20	r Fase afsnijding	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1240 x W38 x H67
212854 Inspire 1200 Wit prismatische 4130lm 4000K Ra>80 Fase afsnijding 29W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek				
	Klasse I IP20	Fase afsnijding	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1465 x W38 x H67
212872 Inspire 1500 Wit prismatische 4960lm 4000K Ra>80 Fase afsnijding 35W LED 142 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prismaoptiek				
Accessoires				
	212198 Zwart T-drager plafondbevestiging			L30 x W20 x H5
	212470 Inspire Zwart Hoekmodule flexi			L78 x W38 x H67
	212255 T-profil Wit Ophangrail 600mm			L596 x W35 x H17
	212471 Inspire Wit Hoekmodule flexi			L78 x W38 x H67