

Tysnes 66 Connect Wireless



Tysnes Connect Wireless is a sealed, slim LED luminaire designed for storage rooms, garages, and parking facilities, featuring an integrated Connect Wireless driver for smart, energy-efficient lighting control. The luminaire is used in combination with other SG Connect devices such as sensors or Connect Switch. Lighting control is easily configured via the SG Connect Commissioning App, and devices communicate wirelessly over Zigbee for flexible, scalable control. Tysnes Connect Wireless offers low power consumption, high light output, and long service life. It can be mounted directly on the ceiling using robust steel clips or with wire suspension. Cable entry at both ends and a knockout for rear cabling simplify installation. The series is available in two lengths to suit different needs.

Tysnes 66 Connect Wireless



Product- en omgevingsbeelden



Artikel		Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	120055	Klasse II	Connect Wireless	Opbouw, Indoor 3-polig schroefloos klemmenblok met 3x2,5mm² doorvoerbedrading	L1200 x W85 x H80
	Tysnes 66 Connect 1200 Grijs	IP66			
	5530lm 4000K Ra>80 Connect	IK10			
	Wireless				
	32W LED				
	173 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	Beam: 121°, Direct, Opaal				
	120056	Klasse II	Connect Wireless	Opbouw, Indoor 3-polig schroefloos klemmenblok met 3x2,5mm² doorvoerbedrading	L1500 x W85 x H80
	Tysnes 66 Connect 1500 Grijs	IP66			
	5560lm 4000K Ra>80 Connect	IK10			
	Wireless				
	32W LED				
	174 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	Beam: 121°, Direct, Opaal				
Accessoires					
	8249044900				L19 x W25 x H150
	Pendelkit 2x5m				
	8249044913				L100 x W98 x H95
	Bevestigingsset voor schuine montage				