

Lineal Surface Connect



Version of Lineal Surface which comes complete with driver and integrated wireless SG Connect sensor. The sensor is discreetly positioned at the edge, switches on when it detects movement and switches off after a pre-selected period of time to save energy. The sensor also includes an integrated daylight sensor. If this function is activated, the sensor will constantly work to provide the desired amount of light in its work area. The lighting control is easy to configure using the SG Connect Commissioning App, and the luminaire can be used individually or as part of a larger system, which can easily be enlarged or reconfigured as needed.

Product- en omgevingsbeelden



Lineal Surface Connect



Artikelcode



Artikel	Bescherming	Regelapparatuur	Montage/Aansluiting	Afmetingen
 9341000675 Lineal surface 1400 Wit 2320lm 3000K Ra>80 Connect 21W LED 110 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,	Klasse I IP20	Connect	Opbouw, Indoor	L1472 x W42 x H70
 9341000818 Lineal surface 1120 Wit 1870lm 3000K Ra>80 Connect 17W LED 110 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,	Klasse I IP20	Connect	Opbouw, Indoor	L1192 x W42 x H70
 9341000882 Lineal surface 840 Wit 1380lm 3000K Ra>80 Connect 13W LED 106 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,	Klasse I IP20	Connect	Opbouw, Indoor	L912 x W42 x H70
Accessoires				
 8241000347 Lineal Wall Extension kit Wit				L115 x W93 x H64
 8241000355 Lineal T-plafond Extension kit Wit				L120 x W94 x H65
 8249045116 Lineal Pendelkit 1 x 2m				