

Hurdal Connect



Hurdal Connect is a compact and stylish ceiling and wall luminaire featuring an integrated SG Connect sensor for smart and energy-efficient lighting control. The sensor switches the light on when motion is detected and off after a defined time period, delivering significant energy savings. A built-in daylight sensor can be activated to maintain the desired light level at all times. Configuration is simple via the SG Connect Commissioning App, and the luminaire can be used as a standalone unit or as part of a larger system that can easily be expanded or reconfigured as needed. Hurdal Connect combines high performance with easy installation. It mounts directly on ceilings or walls, with cable entry at both ends and in the middle, and through-wiring ensures quick and efficient connection. The luminaire is IP44-rated and features a robust steel housing with aluminum end caps for long-lasting and reliable operation.

Hurdal Connect



Product- en omgevingsbeelden





Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	113126	Connect	Opbouw, Indoor 3-polig schroefloos klemmenblok met 3x2,5mm ² doorvoerbedrading	L600 x W72 x H76
	Hurdal Connect 600 Wit 1590lm			
	3000K Ra>80 Connect			
	12W LED			
	133 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct, Opaal			
	113127	Connect	Opbouw, Indoor 3-polig schroefloos klemmenblok met 3x2,5mm ² doorvoerbedrading	L1200 x W72 x H76
	Hurdal Connect 1200 Wit 3460lm			
	3000K Ra>80 Connect			
	24W LED			
	144 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct, Opaal			
	113128	Connect	Opbouw, Indoor 3-polig schroefloos klemmenblok met 3x2,5mm ² doorvoerbedrading	L1500 x W72 x H76
	Hurdal Connect 1500 Wit 4640lm			
	3000K Ra>80 Connect			
	31W LED			
	150 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct, Opaal			