

Ecoline D/I



EcoLine D/I is a slim and stylish suspended luminaire that is designed for quick and easy installation. Direct light with three layer optical system for glare-free light, combined with indirect light with a wide beam angle, gives an efficient light perfectly suited for offices, schools and public buildings. Solid luminaire housing made from powder-coated steel. Optional integrated emergency light upon request.

Ecoline D/I



Product- en omgevingsbeelden



Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	212804	Klasse I	DALI-2	L1235 x W166 x H58
	EcoLine 1200 Wit D/I 4650lm 3000K	IP20	Ophanging, Indoor	
	Ra>80 DALI-2		2 X 2 m kabelkit	
	32W LED		Kabel 5x0,75mm ² 2,5m	
	145 lm/W SDCM:3			
	L90/B10>100,000, L96>50,000			
	Direct/Indirect, Opalprisma			
	212806	Klasse I	DALI-2	L1600 x W166 x H58
	EcoLine 1600 Wit D/I 5430lm 3000K	IP20	Ophanging, Indoor	
	Ra>80 DALI-2		2 X 2 m kabelkit	
	35W LED		Kabel 5x0,75mm ² 2,5m	
	155 lm/W SDCM:3			
	L90/B10>100,000, L96>50,000			
	Direct/Indirect, Opalprisma			
	212812	Klasse I	Niet dimbaar	L1235 x W166 x H58
	EcoLine 1200 Wit D/I 4650lm 3000K	IP20	Ophanging, Indoor	
	Ra>80 Niet dimbaar		2 X 2 m kabelkit	
	32W LED		Kabel 3x0,75mm ² 2,5m	
	145 lm/W SDCM:3			
	L90/B10>100,000, L96>50,000			
	Direct/Indirect, Opalprisma			
	212814	Klasse I	Niet dimbaar	L1600 x W166 x H58
	EcoLine 1600 Wit D/I 5430lm 3000K	IP20	Ophanging, Indoor	
	Ra>80 Niet dimbaar		2 X 2 m kabelkit	
	35W LED		Kabel 3x0,75mm ² 2,5m	
	155 lm/W SDCM:3			
	L90/B10>100,000, L96>50,000			
	Direct/Indirect, Opalprisma			
	212805	Klasse I	DALI-2	L1235 x W166 x H58
	EcoLine 1200 Wit D/I 4850lm 4000K	IP20	Ophanging, Indoor	
	Ra>80 DALI-2		2 X 2 m kabelkit	
	32W LED		Kabel 5x0,75mm ² 2,5m	
	152 lm/W SDCM:3			
	L90/B10>100,000, L96>50,000			
	Direct/Indirect, Opalprisma			
	212807	Klasse I	DALI-2	L1600 x W166 x H58
	EcoLine 1600 Wit D/I 5640lm 4000K	IP20	Ophanging, Indoor	
	Ra>80 DALI-2		2 X 2 m kabelkit	
	35W LED		Kabel 5x0,75mm ² 2,5m	
	161 lm/W SDCM:3			
	L90/B10>100,000, L96>50,000			
	Direct/Indirect, Opalprisma			

Artikel	Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	Klasse I IP20	Niet dimbaar	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1235 x W166 x H58
EcoLine 1200 Wit D/I 4850lm 4000K Ra>80 Niet dimbaar 32W LED 152 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprisma				
	Klasse I IP20	Niet dimbaar	Ophanging, Indoor 2 X 2 m kabelkit Kabel 3x0,75mm ² 2,5m	L1600 x W166 x H58
EcoLine 1600 Wit D/I 5640lm 4000K Ra>80 Niet dimbaar 35W LED 161 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Opalprisma				