

Disc 480 D/I



Disc 480 D/I is an energy efficient and stylish surface-mounted luminaire with a slim profile, providing any room with a modern and refined look. Opal prismatic diffuser ensures glare-free and comfortable lighting with a decorative indirect light. It is possible to choose between 3000K/4000K with the connection cable. Disc 480 D/I is produced in durable aluminium and polycarbonate. Installation is simple, thanks to the quick connection between the luminaire and the backplate, which can be mounted directly onto all standard ceiling boxes. Visible cabling also possible.

Disc 480 D/I



Product- en omgevingsbeelden



Artikel		Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	606201	Klasse II	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø467 x H62
	Disc 480 Zwart D/I 3940lm 2700K	IP20			
	Ra>80 Fase afsnijding	IK10			
	34W LED				
	116 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	606200	Klasse II	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø467 x H62
	Disc 480 Wit D/I 4220lm 2700K	IP20			
	Ra>80 Fase afsnijding	IK10			
	34W LED				
	124 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	606205	Klasse II	DALI-2 / Push Dim	Opbouw, Indoor Schroefloos klemmenblok	Ø467 x H62
	Disc 480 Zwart D/I 4000/4270lm	IP20			
	3000/4000K Ra>80 DALI-2 / Push	IK10			
	Dim				
	34W LED				
	118 lm/W SDCM:3				
	606209	Klasse II	Sensor Dim	Opbouw, Indoor Schroefloos klemmenblok	Ø467 x H62
	Disc 480 Zwart D/I 4000/4270lm	IP20			
	3000/4000K Ra>80 Sensor Dim	IK10			
	34W LED				
	118 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	606182	Klasse II	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø467 x H62
	Disc 480 Zwart D/I 4000/4270lm	IP20			
	3000/4000K Ra>80 Fase afsnijding	IK10			
	34W LED				
	118/126 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	606204	Klasse II	DALI-2 / Push Dim	Opbouw, Indoor Schroefloos klemmenblok	Ø467 x H62
	Disc 480 Wit D/I 4160/4420lm	IP20			
	3000/4000K Ra>80 DALI-2 / Push	IK10			
	Dim				
	34W LED				
	122 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	Beam: 85°, Direct, Opalprisma				

Artikel		Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	606208	Klasse II	Sensor Dim	Opbouw, Indoor	Ø467 x H62
	Disc 480 Wit D/I 4160/4420lm 3000/4000K Ra>80 Sensor Dim 34W LED 122 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprisma	IP20 IK10		Schroefloos klemmenblok	
	606180	Klasse II	Fase afsnijding	Opbouw, Indoor	Ø467 x H62
	Disc 480 Wit D/I 4160/4420lm 3000/4000K Ra>80 Fase afsnijding 34W LED 122/130 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprisma	IP20 IK10		Schroefloos klemmenblok	
Accessoires					
	606095				L5000 x W102 x H22
	Disc/Frosta Zwart Pendel Adapter				
	606094				L5000 x W102 x H22
	Disc/Frosta Wit Pendel Adapter				