

Disc 290 D/I



Disc 290 D/I is an energy efficient and stylish surface-mounted luminaire with a slim profile, providing any room with a modern and refined look. Opal prismatic diffuser ensures glare-free and comfortable lighting with a decorative indirect light. It is possible to choose between 3000K/4000K with the connection cable. Disc 290 D/I is produced in durable aluminium and polycarbonate. Installation is simple, thanks to the quick connection between the luminaire and the backplate, which can be mounted directly onto all standard ceiling boxes. Visible cabling also possible.

Disc 290 D/I



Product- en omgevingsbeelden



Artikel		Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	606203	Klasse II	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø290 x H62
	Disc 290 Zwart D/I 1860lm 2700K	IP20			
	Ra>80 Fase afsnijding	IK10			
	18W LED				
	103 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	Beam: 85°, Direct, Opalprisma				
	606202	Klasse II	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø290 x H62
	Disc 290 Wit D/I 1940lm 2700K	IP20			
	Ra>80 Fase afsnijding	IK10			
	18W LED				
	108 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	Beam: 85°, Direct, Opalprisma				
	606207	Klasse II	DALI-2	Opbouw, Indoor Schroefloos klemmenblok	Ø290 x H62
	Disc 290 Zwart D/I 1840/1970lm	IP20			
	3000/4000K Ra>80 DALI-2	IK10			
	18W LED				
	102 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	Beam: 85°, Direct, Opalprisma				
	606211	Klasse II	Sensor Dim	Opbouw, Indoor Schroefloos klemmenblok	Ø290 x H62
	Disc 290 Zwart D/I 1840/1970lm	IP20			
	3000/4000K Ra>80 Sensor Dim	IK10			
	18W LED				
	102 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	Beam: 85°, Direct, Opalprisma				
	606185	Klasse II	Fase afsnijding	Opbouw, Indoor Schroefloos klemmenblok	Ø290 x H62
	Disc 290 Zwart D/I 1840/1970lm	IP20			
	3000/4000K Ra>80 Fase afsnijding	IK10			
	18W LED				
	102/109 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	Beam: 85°, Direct, Opalprisma				
	606206	Klasse II	DALI-2	Opbouw, Indoor Schroefloos klemmenblok	Ø290 x H62
	Disc 290 Wit D/I 2000/2140lm	IP20			
	3000/4000K Ra>80 DALI-2	IK10			
	18W LED				
	111 lm/W SDCM:3				
	L80/B20>100,000, L90>50,000				
	Beam: 85°, Direct, Opalprisma				

Artikel		Bescherming	Regelapparaat	Montage/Aansluiting	Afmetingen
	606210	Klasse II	Sensor Dim	Opbouw, Indoor	Ø290 x H62
	Disc 290 Wit D/I 2000/2140lm 3000/4000K Ra>80 Sensor Dim 18W LED 111 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprisma	IP20 IK10		Schroefloos klemmenblok	
	606184	Klasse II	Fase afsnijding	Opbouw, Indoor	Ø290 x H62
	Disc 290 Wit D/I 2000/2140lm 3000/4000K Ra>80 Fase afsnijding 18W LED 111/119 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprisma	IP20 IK10		Schroefloos klemmenblok	
Accessoires					
	606095				L5000 x W102 x H22
	Disc/Frosta Zwart Pendel Adapter				
	606094				L5000 x W102 x H22
	Disc/Frosta Wit Pendel Adapter				