




Design: F Mark Recessed or surface-mounted using accessories, low profile 35 mm height, direct LED luminaire, 592x592 mm for mounting in visible T-rail ceilings or 599x599 mm for concealed ceiling systems. With unique energy efficiency (up to 112 lm/W), collimated TIR optics with angled illuminated edge made of sheet steel. Precise low unified glare rating (UGR)

Produkt- und Umgebungsbilder



Artikel	Schutzklasse	Controller	Montage/Anschluss	Grösse
Treiber				
 820083 Sense Driver Weiss 3000lm 25W 700mA DALI-2 / Push Dim 25W 100.000	Klasse II IP20	DALI-2 / Push Dim	Einbau, Indoor 5 pol Linect / Anschlussklemme	L124 x W79 x H22
 8246093158 Molior Line 1 Line / 1 Corner 14W 300mA Nicht dimmbar				
 8246093815 Molior Line 2 Line / 4 Corner 36W 700mA Nicht dimmbar				L125 x H35
Zubehör				
 212935 Sense/DiLED 625x625 Weiss Universal adapter steelplate				L620 x W620 x H11
 8249044557 625x625 Weiss Gesägte Decken/Troldtekt Einbaurahmen				L625 x W625 x H55
 8249045006 Sense 600x600 Weiss Gesägte Decken/Troldtekt Einbaurahmen				L640 x W640 x H40
 8246094429 Notlichtbox Treiber DALI / EM Self test, DALI Einzelbatteriebaustein 3Std				L270 x W75 x H35
 8246094364 Notlichtbox On-Off/Phasenabschnitt / EM Self test, Notlicht 3 stunden				L270 x W75 x H35
 8246094500 Notlichtbox Treiber DALI / EM DALI/Self test, Notlicht 3 stunden				L270 x W75 x H35